

350 GHz Holographic Surface for Single- and Multi-focusing

Kuznetsov, Sergey A.; Astafev, Mikhail A.; Beruete, M.; Navarro-Cia, Miguel

DOI:

[10.1109/USNC-URSI.2015.7303420](https://doi.org/10.1109/USNC-URSI.2015.7303420)

License:

Other (please specify with Rights Statement)

Document Version

Peer reviewed version

Citation for published version (Harvard):

Kuznetsov, SA, Astafev, MA, Beruete, M & Navarro-Cia, M 2015, 350 GHz Holographic Surface for Single- and Multi-focusing. in *Radio Science Meeting (Joint with AP-S Symposium), 2015 USNC-URSI*. Institute of Electrical and Electronics Engineers (IEEE), pp. 136. <https://doi.org/10.1109/USNC-URSI.2015.7303420>

[Link to publication on Research at Birmingham portal](#)

Publisher Rights Statement:

(c) 2015 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other users, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works for resale or redistribution to servers or lists, or reuse of any copyrighted components of this work in other works

General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

350 GHz Holographic Surface for Single- and Multi-focusing

Sergei A. Kuznetsov^(1,2,3), Mikhail A. Astafev^(1,2), Miguel Beruete⁽⁴⁾, and Miguel Navarro-Cía*^(5,6)

(1) Novosibirsk State University, Novosibirsk, 630090, Russian Federation

(2) Budker Institute of Nuclear Physics SB RAS, Novosibirsk, 630090,
Russian Federation

(3) Institute of Semiconductor Physics SB RAS, Novosibirsk Branch
“TDIAM”, Novosibirsk, 630090, Russian Federation

(4) Universidad Pública de Navarra, 31006 Pamplona, Spain

(5) Imperial College London, London SW7 2AZ, UK, m.navarro@imperial.ac.uk

(6) University College London, London WC1E 7JE, UK

Reflectors are the preferred high-gain antenna for ground base stations and radar applications. However, they are bulky and heavy for airborne applications. Hence, planar arrays such as microstrip antenna arrays are favored in airborne use. Unfortunately, losses in the array feeding network are unacceptable at Terahertz (THz) frequencies due to the significant absorption of any material/substrate in this range (D. Grischkowsky et al., J. Opt. Soc. Am. B, 7, 2006, 1990). Therefore, high-gain reflectarrays are the preferred practical solution for high data rate THz airborne applications.

The spatial varying reflection of a reflectarray (also known as holographic surface) can be easily engineered to have specific radiation patterns. This is a powerful idea that can be also exploited to manipulate Gaussian beams. Here, we show at the atmospheric window of 350 GHz how to focus an incident Gaussian beam into a single or four different focal points using holographic surfaces (S.A. Kuznetsov et al., Sci. Rep., 5, 7738, 2015). The holographic surfaces consist of a patterned layer lying on a grounded dielectric slab. The dimension of each unit cell square-pixel is $\sim\lambda_0/3$ to minimize grating lobes as well as phase errors while the required 360 degree phase variation is still achievable with simple pixel patterns. The 360 degree variation required in the surface is achieved via topological morphing of the surface pattern from metallic patches to U-shaped and split-ring resonators, making the design polarization dependent. The easy-to-code and robust Gerchberg-Saxton holographic algorithm is utilized in this work to synthesize the required reflection phase distribution. The holographic surface is illuminated by a Gaussian beam under an incidence angle of 45 degree to avoid blockage. The detection at the focal plane is done using a pyro-electric detector mounted on an xy -translation stage. A diffraction efficiency (i.e., ratio of the power diffracted into a chosen diffraction order to the power of the incoming wave beam) $\sim 80\%$ and a -3 dB bandwidth (i.e., -3dB fall relative to the peak magnitude) $\sim 14\%$ and $\sim 9\%$ for 1-spot and 4-spots designs, respectively, are achieved experimentally. We demonstrate then a high-performance solution for creating purely flat, thin, light-weight and relatively inexpensive passive beam-shaping and beam-focusing devices for the THz band.