UNIVERSITY BIRMINGHAM University of Birmingham Research at Birmingham

Microscale flow dynamics of ribbons and sheets

Montenegro-Johnson, Thomas; Koens, Lyndon; Lauga, Eric

DOI: 10.1039/C6SM02105K

License: None: All rights reserved

Document Version Peer reviewed version

Citation for published version (Harvard): Montenegro-Johnson, T, Koens, L & Lauga, E 2016, 'Microscale flow dynamics of ribbons and sheets', *Soft Matter.* https://doi.org/10.1039/C6SM02105K

Link to publication on Research at Birmingham portal

General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

•Users may freely distribute the URL that is used to identify this publication.

Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)

•Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

Microscale Flow Dynamics of Ribbons and Sheets

Thomas D. Montenegro-Johnson,^{*a,b,c*} Lyndon Koens^{*b*} and Eric Lauga^{*b*}

Numerical study of the hydrodynamics of thin sheets and ribbons presents difficulties associated with resolving multiple length scales. To circumvent these difficulties, asymptotic methods have been developed to describe the dynamics of slender fibres and ribbons. However, such theories entail restrictions on the shapes that can be studied, and often break down in regions where standard boundary element methods are still impractical. In this paper we develop a regularised stokeslet method for ribbons and sheets in order to bridge the gap between asymptotic and boundary element methods. The method is validated against the analytical solution for plate ellipsoids, as well as the dynamics of ribbon helices and an experimental microswimmer. We then demonstrate the versatility of this method by calculating the flow around a double helix, and the swimming dynamics of a microscale "magic carpet".

1 Introduction

At microscopic scales, fluid flow is governed by the Stokes flow equations: inertialess, and kinematically reversible.¹ The dynamics of microscale objects in Stokes flow is highly dependent upon their geometry; for example, the drag anisotropy of slender rods can cause them to translate at an angle to gravity when settling,² and is crucial for the swimming of microorganisms with flagellar filaments.^{3,4} But for many systems of medical or industrial significance, this geometric dependence can be difficult to compute.

The Boundary Element Method (BEM)^{5,6} is commonly employed in studies of microscale biofluiddynamics.^{7–10} In BEM, the Stokes flow equations are transformed into an integral of Green's functions over the domain boundaries.⁶ These boundaries are discretised or "meshed" into typically triangular elements (Fig. 1e), and the boundary integral is then calculated over each mesh element to form a linear system which can be solved.

However, when there is a separation of length scales in the object being studied (Fig. 1), as with for instance the slender flagellum of bacteria or spermatozoa, resolving each scale with the boundary element method can result in very large linear systems. Early work by Hancock¹¹ treated the slender flagellum of seaurchin spermatozoa as a line of point forces, from which local resistive force theories were derived, ^{12,13}, which could be generalised to any cross-sectional shape (Fig. 1b)¹⁴. However this local treatment required the cross-sectional length scale of the filament, *w*, to be exponentially smaller than the centreline length, $\ell (1 \gg 1/\log(\ell/w))$, with small curvature.

Building on this work, Slender Body Theory (SBT) was developed to determine the flow from such filaments to algebraic accuracy.^{15,16} These models describe the hydrodynamics of a filament, with circular cross section, by expanding the flow from a line of point forces placed along the filament's centreline and has been used extensively to examine swimming and pumping in microscale biological systems.^{17–20}

Recently, slender-ribbon theory (SRT) was developed to accurately explore the microscale hydrodynamics of slender ribbons.^{21,22} This method expanded on the work of Johnson¹⁶ and so captures the non-local interactions of the shape and is accurate to order w/ℓ . The slenderness condition in SRT is contingent on the assumption that all three internal length scales of the ribbon, the length, ℓ , width, w, and thickness, h, are separated $\ell \gg w \gg h$ (Fig. 1c), and the leading order flow is found by asymptotically expanding the flow from a plane of point forces representing the ribbon with respect to these length scales. The flow at the ribbon's surface is then given in terms of a line integral²² of unknown forces, as in SBT, which can be inverted to determine the force on the fluid. This technique allows the asymptotic exploration of a range of ribbon structures, such as artificial microswimmers comprising a magnetic head and a ribbon tail.^{23–25}

While SRT captures the leading order behaviour of many ribbon shapes, it is unsuitable for highly-twisted ribbons, or those with a very curved centreline. Similarly, the asymptotic treatment of the "slender-ribbon" limit $\ell \gg w \gg h$ prevents SRT from capturing the dynamics of sheets ²⁶ with $\ell \sim w \gg h$ (Fig. 1d), and causes the theory to break down before a standard boundary element approach becomes practical.

In this paper we develop Ribbon-BEM (RiBEM), a method to bridge the gap between SRT and BEM that is capable of solving the dynamics of both highly twisted and curved ribbons as well as sheets. Inspired by previous treatments of cilia and flagella as line distributions of regularised forces²⁷ and SRT, we generate a two-dimensional manifold surface mesh representing the ribbon centreplane, and account for the finite thickness of the sheet via the regularisation parameter ε of a surface distribution of regularised forces.

The method is validated against analytical solutions for a trans-

 ^a School of Mathematics, University of Birmingham, Edgbaston, Birmingham, B15 2TT
 ^b Department of Applied Mathematics and Theoretical Physics, University of Cambridge,

Centre for Mathematical Sciences, Wilberforce Rd, Cambridge, CB3 0WA

^c Email for correspondance: t.d.johnson@bham.ac.uk



Fig. 1 Classes of shapes in Stokes flow. (a) Slender Body Theory (SBT) is an appropriate choice for long, slender bodies of circular cross-section. Examples are the flagella of bacteria or spermatozoa. (b) When this cross-section is flattened slightly, but the width and thickness are still comparable, only local drag theory (RFT) has so far been developed ¹⁴; there is no non-local equivalent to SBT in this case, but though inefficient, boundary element methods may still be employed. An example of such a squashed slender body is the trematode worm *Schistosoma mansoni*, responsible for Schistosomiasis. (c) Slender Ribbon Theory (SRT) is appropriate when all three intrinsic length scales are separated $\ell \gg w \gg h$, which can occur in artificial microswimmer design. (d) The current study sits in the domain between SRT and the Boundary Element Method (BEM) (e).

lating plate ellipsoid, and then compared with previous BEM²⁸ calculations for the hydrodynamics of twisted helices and the resistance matrix of an experimental ribbon-shaped artificial microswimmer.²⁴ We then demonstrate the flexibility of the method by calculating the flow around a sedimenting double helix with a curved centreline, before finally considering the swimming dynamics of a finite waving sheet²⁶ or "magic carpet".

2 Mathematical model

We will consider microscale ribbons and sheets, for which the dynamics of the surrounding fluid is well-modelled by the Stokes flow equations

$$\mu \nabla^2 \mathbf{u} - \nabla p = 0, \quad \nabla \cdot \mathbf{u} = 0, \tag{1}$$

where \mathbf{u} is the fluid velocity and p the dynamic pressure.

To solve these equations (1), we employ the regularised stokeslet boundary element method.^{27,29} The velocity at a point \mathbf{x}_0 in the domain is given by integrals of stokeslets **S** and stresslets **T** over the swimmer surface, *S*,

$$\int_{V} u_{j}(\mathbf{x})\phi_{\varepsilon}(\mathbf{x}-\mathbf{x}_{0}) \,\mathrm{d}V_{x} = \int_{S} S_{ij}^{\varepsilon}(\mathbf{x},\mathbf{x}_{0}) f_{i}(\mathbf{x})$$
$$-u_{i}(\mathbf{x})T_{ijk}^{\varepsilon}(\mathbf{x},\mathbf{x}_{0})n_{k}(\mathbf{x}) \,\mathrm{d}S_{x}, \quad (2)$$

for unknown surface tractions, **f**, and surface velocity **u**. The lefthand side is a volume integral over the fluid domain of the velocity multiplied by a 'blob' regularisation of the Dirac δ -function.

For rigid body motions, or where the volume of a swimmer is constant over its beat, we have the condition 6

$$\int_{S} \mathbf{u}(\mathbf{x}) \cdot \mathbf{n}(\mathbf{x}) \, \mathrm{d}S_x = 0. \tag{3}$$

This condition also holds to a very good approximation for flexible

yet inextensible swimmers provided the thickness $h \ll w, l$, since the volume of such swimmers varies only very slightly. Under condition (3), the boundary integral equation (2) can then be rewritten in terms of a modified force density

$$u_j(\mathbf{x}_0) = \int_S S_{ij}^{\mathcal{E}}(\mathbf{x}, \mathbf{x}_0) f_i(\mathbf{x}) \, \mathrm{d}S_x,\tag{4}$$

which reduces computational complexity significantly. In our model, we will impose velocities at the depth midplane and use the regularisation to account for the finite thickness of the swimmer in a similar manner to Smith's treatment of slender bodies;²⁷ we thus employ the "single layer" boundary integral equation (4). The regularisation function for the blob driving forces is given by²⁹

$$\phi_{\varepsilon}(\mathbf{x} - \mathbf{x}_0) = \frac{15\varepsilon^4}{8\pi r_{\varepsilon}^7}, \quad r_{\varepsilon}^2 = r^2 + \varepsilon^2,$$
(5)

where $r_i = (\mathbf{x} - \mathbf{x}_0)_i$, $r = |\mathbf{x} - \mathbf{x}_0|$ and $\varepsilon \ll 1$. For such a blob force, the regularised stokeslet is then

$$S_{ij}^{\varepsilon}(\mathbf{x}, \mathbf{x}_0) = \frac{\delta_{ij}(r^2 + 2\varepsilon^2) + r_i r_j}{r_{\varepsilon}^3}.$$
 (6)

We will discretise the boundary integral equation (4) over mesh of geometrically piecewise-quadratic triangles. The unknown tractions **f** will be discretised as piecewise-constant $f_i[1], \ldots, f_i[N]$ over each element $E[1], \ldots, E[N]$, where $E = E[1] \cup \ldots \cup E[N]$ is the surface mesh of N elements describing the ribbon or sheet. This discretisation yields a matrix system of the form

$$u_j(\mathbf{x}_0) = \sum_{n=1}^N f_i[n] \int_{E[n]} S_{ij}^{\varepsilon}(\mathbf{x}, \mathbf{x}_0) \, \mathrm{d}S_x, \quad \mathbf{x}_0 \in E[m], \tag{7}$$

where \mathbf{x}_0 is the centroid of element E[m], with m = 1,...,N and i, j, = 1, 2, 3. This yields 3N equations for the 3N unknown surface tractions. Element integrals of the regularised stokeslets are per-

formed using adaptive Fekete quadrature. Code is implemented in matlab, and adapted from the authors' previous work.³⁰ We will now proceed with a validation of this method against previous analytical and numerical results.

3 Validation

3.1 Plate ellipsoids

We begin by considering the resistance of a plate ellipsoid to the 6 principal translations and rotations. The total drag *F* on an ellipsoid with semi-axes $\{\ell, w, h\}$, where without loss of generality $\ell \ge w \ge h$, translating at speed *U* in direction ℓ is given by³¹

$$\frac{F}{\pi\mu U} = \frac{16}{\phi + \zeta_\ell \ell^2},\tag{8}$$

while the torque *T* due to a rotation at rate Ω about ℓ is given by

$$\frac{T}{\pi\mu\Omega} = \frac{16}{3} \frac{w^2 + h^2}{w^2 \zeta_w + h^2 \zeta_h},$$
(9)

where

$$\phi = \int_0^\infty \frac{\mathrm{d}x}{\sqrt{(\ell^2 + x)(w^2 + x)(h^2 + x)}},$$
(10a)

$$\zeta_{\ell} = \int_0^\infty \frac{\mathrm{d}x}{(\ell^2 + x)\sqrt{(\ell^2 + x)(w^2 + x)(h^2 + x)}},$$
 (10b)

$$\zeta_w = \int_0^\infty \frac{\mathrm{d}x}{(w^2 + x)\sqrt{(\ell^2 + x)(w^2 + x)(h^2 + x)}},$$
 (10c)

$$\zeta_h = \int_0^\infty \frac{\mathrm{d}x}{(h^2 + x)\sqrt{(\ell^2 + x)(w^2 + x)(h^2 + x)}}.$$
 (10d)

The regularisation ε is chosen such that the thickness of the semiaxis $h = \varepsilon$, in the same way that ε is used as a proxy for filament thickness in regularised stokeslet slender body theory²⁷. In practice, provided $\ell, w \gg h$, the drag is fairly insensitive to this choice; substituting values of $\ell = 1, w = 0.1$ then h = 0.001, 0.0005 into the above equations, we see less than a 0.3% difference in all 6 components of the resistance matrix. Note that since we keep the regularisation constant over the entire surface, our model in fact represents an elliptical disk of finite thickness. Nonetheless, for very thin discs, we expect this discrepancy to be small.

Figure 2a shows a particular drag component, the broadside drag F_h , on a thin plate ellipsoid of semi-axis length $\ell = 1$ and thickness h = 0.005 as a function of varying width w. The analytical solution is compared to numerical solutions calculated via RiBEM, SRT, and SBT assuming the radius of the filament is given by w. The RiBEM meshes for ellipse-based geometries are generated using routines adapted from DistMesh³², with a desired uniform mesh element edge length dependent upon the area of the ellipse, $A = \pi \ell w$, so that $E_l = \sqrt{\pi \ell w / 500}$. Since an ideal mesh comprises equilateral triangles, which have an area $A_t = \sqrt{3}E_l^2/4 \approx E_l^2/2$, this choice results in uniform meshes with approximately N = 1000 elements for each value of width w.

In the region $1 \ge w \ge 0.3$, $\ell \sim w \gg h$, and the geometry is a sheet as in figure 1d. RiBEM performs very favourably in this régime, while the asymptotic solutions of SRT and SBT significantly over-

(a) Broadside drag on plate ellipsoids







Fig. 2 (a) Comparing methods of evaluating the broadside drag (direction demonstrated on the inset ellipsoid) F_h on a plate ellipsoid of length $\ell = 1$, thickness h = 0.005, and varying width w. RiBEM performs well until $w \sim 0.1$ in a region roughly corresponding to figure 1d, whereafter it because difficult to resolve meshes. SRT is thereafter very accurate for this component in the region corresponding to figure 1c, but is finally superceded by SBT once width and thickness are comparable (the region of figure 1b). At the bottom of the range, w = h = 0.005 and SBT gives the drag exactly. (b) The percentage error in the principal components of the resistance matrix as calculated by RiBEM for slightly thicker plate ellipsoids with $\ell = 1, h = 0.01$ and varying w, showing good agreement with analytical results.

estimate the drag. As *w* decreases, we begin to separate all three length scales $\ell \gg w \gg h$ (Fig. 1c), and for $0.3 \ge w \ge 0.1$, SRT has a similarly high accuracy to RiBEM, whereas SBT is still significantly off. At around w = 0.1, $\ell \gg w$, and it becomes increasingly difficult to numerically resolve the geometry using RiBEM, as retaining resolution in the *w* direction leads to a very fine mesh in the ℓ direction. This results in large matrix systems with RiBEM, and so SRT becomes the appropriate choice. At around $w = 0.01 \sim h$, we no longer have separation of scales between the width and thickness $\ell \gg w \sim h$ and the slender ribbon assumption is no-longer valid. In this régime, (Fig. 1a,b) SBT becomes the current most accurate choice, finally recovering the drag exactly when w = 0.005 = h. Theses results demonstrate the need

to choose the correct method based on the separation of length scales in the geometry being considered, as shown in figure 1.

In figure 2b, we validate RiBEM for all 6 values of the resistance matrix for a thicker ellipsoid with $\ell = 1, h = 0.01$, and $w \in [1, 0.1]$. Finding all 6 diagonal values of the resistance matrix with approximately N = 1000 elements took approximately 15 seconds for each value of w on a Dell Optiplex 9020 desktop computer. Even for this relatively coarse discretisation, the error in the mobility tensor is small, less than 3% for all components.

3.2 Helical ribbons

Recently, Keaveny and Shelley²⁸ explored how a helical ribbon's configuration and aspect ratio, h/w, changed its propulsive capability. This investigation used a boundary element method and considered ribbons with an ellipsoidal cross-section and the parametrisation

$$\mathbf{r}(s_1) = \{r_h \cos(ks_1), r_h \sin(ks_1), \alpha s_1\},$$
(11)

$$\mathbf{\hat{T}}(s_1) = \cos(\gamma)\mathbf{\hat{b}} - \sin(\gamma)\mathbf{\hat{n}}.$$
(12)

Here, $\mathbf{r}(s_1)$ is the helix centreline, r_h is the helix radius, $k = 4\pi$ is the helix wavenumber, and α is the cosine of the helix angle. The unit vector $\mathbf{\hat{T}}(s_1)$ points towards the major axis of the ribbon cross-section, while γ is the angle between the helix axis and $\mathbf{\hat{T}}$. Finally, $\mathbf{\hat{n}}$ and $\mathbf{\hat{b}}$ are the normal and binormal vectors to the helix centreline. Figure 3a shows two example ribbons generated by this parameterisation.

The thinnest of the ribbons considered by Keaveny and Shel ley^{28} , with h/w = 1/4, lie at the borderline where traditional boundary element techniques can become computationally infeasible. However, at these aspect ratios or finer, RiBEM is an effective alternative. Figure 3b shows the effect of varying $0 \le \gamma \le \pi/2$ on configurations with $\alpha = 0.5$, 0.75 and 0.9, with h/w = 1/4 for Keaveny and Shelley's results with an ellipsoidal cross-section compared with RiBEM results for $\varepsilon/w = 1/5$ for a rectangular cross-section; this aspect ratio is chosen such that the rectangular cross section $4hw \approx \pi hw$ the ellipsoidal cross-section, as $\pi/16 = 0.196 \approx 1/5$. These results are in very good agreement, indicating that even for relatively thick ribbons, this choice of $\varepsilon = h$ provides a reasonable proxy for finite thickness with small deviations arising from the difference in cross-sectional shape, which reduce for thinner ribbons. Indeed, it should be noted that for manufacturing purposes, a rectangular cross-section may in fact be preferable, as in the following case.

3.3 A magnetic microhelix

Helical ribbons, similar to those considered above, have recently been used in laboratory settings to create *artificial bacterial flagella* (ABF).²⁴ These ABFs comprise a magnetic head rigidly attached to a helical ribbon tail, and swim when driven by an external rotating magnetic field. The swimming behaviour has in turn been used to experimentally determine the resistance coefficients of such a swimmer,²⁴ which have also been analysed theoretically using SRT²¹ and BEM.³³ The flexibility of RiBEM allows us generate a realistic computational mesh of the experimental





(b) Swimming speed



Fig. 3 The dynamics of helical ribbons. (a) Ribbons given by the parameterisation Eqs. (11) and (12) with $\alpha = 0.5$, and $\gamma = 0$ (left) and $\gamma = \pi/4$ (right). (b) The swimming velocity in response to a unit torque about the helix axis for varying γ . The dashed lines are the results of Keaveny and Shelly²⁸ for ribbons with h/w = 1/4, while the solid lines are the results from RiBEM for ribbons with $\varepsilon/w = 1/5$. The slight discrepancy between these results is likely because the Keaveny results have an elliptical cross-section, where as the RiBEM results are for a flat cross-section.

system (Fig. 4). Indeed, provided that the geometric condition $\ell/h, w/h \gtrsim 5$ holds, the approximate borderline as above between RiBEM and BEM, RiBEM will be an effective method for the computational design and optimisation of low Reynolds number artificial swimmers with ribbon or sheet-like geometries.

In the SRT study of this ABF, the ribbon was treated as asymptotically thin, with the head modelled as a plate ellipsoid without non-local hydrodynamic interactions. In the BEM study, the aspect ratio of h/w = 1/4 overestimated the ribbon thickness by an order of magnitude. We now attempt to use our model in order to resolve differences between the previous studies and the experimental data.

The experimental ABF considered had a slender ribbon tail with an axial length of $L = 38 \ \mu\text{m}$, width $w = 1.8 \ \mu\text{m}$, and thickness $h = 42 \ \text{nm}$, and a square magnetic head with dimensions of 4.5 $\mu\text{m} \times 4.5 \ \mu\text{m} \times 200 \ \text{nm}$. The ribbon was helical, as



Fig. 4 Computational mesh of the magnetic helical microswimmer studied in Ref.²⁴ Note that this mesh differs from previous numerical studies as the edges of the ribbon are not curved and the head is not approximated by an ellipsoid, however these differences do not have much of an effect on the resistance matrix, with the present study agreeing with previous treatments using BEM for a significantly fatter mesh and SRT.

	Exp	SRT	BEM	RiBEM
$R_a (10^{-7} \text{ N.s.m}^{-1})$	1.5	1.04	0.937	0.932
$R_b (10^{-14} \text{ N.s})$	-1.6	-1.32	-1.63	-1.47
$R_c \ (10^{-19} \text{ N.m.s})$	2.3	6.81	10.1	9.91

Table 1 Hydrodynamic resistance coefficients for the ribbon microswimmer. Left: experimental measurements.²⁴ Middle-Left: SRT results assuming $2r_h = 2.8 \ \mu m.^{21}$ Middle-Right: the BEM model swimmer results from Ref.³³ Right: RiBEM result assuming $2r_h = 2.8 \ \mu m.$ The hydrodynamic resistance coefficient R_a relates the drag force experienced parallel to the helical axis from translation in the same direction, whereas R_b is the hydrodynamic force experienced parallel to the helix axis, and R_c is the hydrodynamic torque experienced around the helical axis from rotation around said axis of both the head and the helix.

a ribbon wrapped around a pencil, and had a helix diameter of $2r_h = 2.8 \ \mu m$ immediately after fabrication. We therefore describe this ribbon using Eq. (11), but with $\hat{\mathbf{T}} = \hat{\mathbf{z}}$, where $\hat{\mathbf{z}}$ is the helix axis. The mesh used for the RiBEM calculations, generated using simple custom routines, is shown in figure 4. This mesh is closer to the experimental system than those used in previous studies^{21,33}, since it does not exhibit the curved edges, which are not present in the experiment, found from the ribbon parameterisation based upon Eqs. (11) and (12).

Table 1 lists the experimentally-determined resistance coefficients and the corresponding resistance coefficients of each model. Significantly, we see that all independent theoretical models predict similar values for the resistance coefficients, with slight variations likely due to the details of each model. This result would seem to indicate that the discrepancy was not caused by the approximations present in the previous SRT or BEM studies. The drag coefficient R_a is underpredicted in all models, while the coefficient coupling axial rotation and translation R_b is best captured using the boundary element method or the RiBEM code. The rotational coefficient R_c is overestimated significantly by all three models. Koens and Lauga²¹ hypothesised that the curved edge of the SRT/Keaveny parameterisation might be responsible for this discrepancy. However, since this approximation is not present in our RiBEM model, the source of this discrepancy remains unclear.

4 Results

4.1 A coiled double helix

The helix above is an experimental realisation of the bacterial flagellum: a microscale chiral structure that couples rotation with translation. In the example above, the centreline of the helix is twisted about a central axis, but the ribbon itself is not twisted about its centreline. Centreline twist is another fundamental chirality which can couple rotation and translation, and is observed in nature in, for instance, the double helix of of DNA.

In order to demonstrate the simplicity and flexibility of our method, we now calculate the 6×6 Grand Resistance Matrix (GRM) of a rigid, coiled double helix, and the streamlines resulting from uniform flow past it. The centreline we prescribe for the double helix is given by two straight lines, folding over into the lemniscate of Bernoulli, given by the parametric equation

$$x = \frac{\sqrt{2}\cos t}{\sin^2 t + 1}, \qquad x = \frac{\pm (t \pm \pi/2)}{\sqrt{2}},$$
 (13a)

$$y = \frac{\sqrt{2}\sin t \cos t}{\sin^2 t + 1}, \qquad y = \frac{t \pm \pi/2}{\sqrt{2}},$$
 (13b)

$$t \in (-\pi/2, \pi/2), \qquad t \in [-\pi, -\pi/2], \quad t \in [\pi/2, \pi],$$
 (13c)

with z = 0.1t, $t \in [-\pi, \pi]$. We generate constant twist along this centreline, with $\hat{\mathbf{T}} = \cos(2\pi ks/L)\hat{\mathbf{b}} + \sin(2\pi ks/L)\hat{\mathbf{n}}$ for centreline binormal $\hat{\mathbf{b}}$ and normal $\hat{\mathbf{n}}$. Here, we denote the arclength of the centreline by *s*, which differs from the parametric variable *t*, the length of the centreline *L*, and the wavenumber k = 6. This parametrisation, with a width of w = L/20, produces the folded double helix shown in figure 5.

Setting an arbitrary small thickness of $h = 0.01 \approx w/35$, the resistance matrix for the double helix in this configuration, with a resolution of N = 3200 elements, is given by

[13.0274	0.0002	-0.0002	-0.1688	-0.0017	-0.0017
0.0002	14.0480	0.2342	0.0004	-0.1690	0.2704
-0.0002	0.2343	16.3583	0.0008	-1.4422	0.2710
-0.1688	0.0005	0.0009	11.8006	0.0008	0.0005
-0.0015	-0.1693	-1.4422	0.0004	21.0341	1.9619
0.0018	0.2704	0.2706	0.0005	1.9623	24.4865



(b) Flow around the double helix



Fig. 5 (a) Plan view of a double helix with straight ends, coiled over into a half figure-of-eight. (b) Uniform flow past the double helix, showing streamlines that are deflected as though by an equivalent cylinder, and a few streamlines that follow the twisting surface more closely.

It is worth noting that this is remarkably similar to the resistance matrix of a cylinder extruded along the same centreline, capped by hemispheres, with radius w = L/40 (i.e. half the radius of the ribbon)

[12.7157	-0.0000	0.0000	0.1716	0.0000	0.0000
0.0000	13.6380	0.2477	0.0000	0.0891	-0.3409
0.0000	0.2476	16.0148	-0.0000	-0.9322	-0.2118
0.1716	0.0000	0.0000	11.5256	0.0000	0.0000
-0.0000	0.0891	-0.9325	-0.0000	20.2099	2.2285
-0.0000	-0.3407	-0.2120	0.0000	2.2281	24.4529

with only some very small off-diagonal elements arising from the twisting of the helix not present. This supports previous observations²¹ that the GRM of a double helix is well-modelled by an "average" cylinder. We note however that three of the terms in the DNA coupling sub-matrix have the opposite sign to the cylinder case. This change in sign is due to the twisting of the ribbon's surface creating a different flow pattern. However as these terms are two orders of magnitude smaller than the largest terms in

the GRM, only very accurate experiments will be able to measure them.

The GRM only captures the trajectories of rigid objects, and does not account for detailed flow structures at the ribbon surface or the spatially-dependent force per unit area on the structure. Instantaneous flow streamlines for a sedimenting double helix in the frame in which the body is stationary are shown in figure 5b, revealing intricate patterns and twisting streamlines near the surface. A particularly interesting avenue of future research will be to couple this fully-resolved flow and surface tractions to a constitutive model for the double helix itself. Omori et al. 34 modelled the deformation of a red blood cell, a closed membrane travelling through a micropore, by coupling the standard boundary element method for flow to a finite element solution for a thin hyperelastic membrane representing the cell. Finite element shell computations for open membranes could be coupled to RiBEM in an analogous way, indeed the flexibility of regularised stokeslet methods makes them ideal for coupling with elastic models for structures³⁵.

4.2 Taylor's magic carpet

G. I. Taylor's model of a small-amplitude, infinite swimming sheet³⁶ is often used as an analytical means to study microscale propulsion, and is increasingly being used to examine swimming in non-Newtonian fluids.^{37,38} Furthermore, a finite-sized analogue of Taylor's sheet has recently been developed experimentally,²⁶ driven by an applied magnetic field as a means of achieving controlled locomotion at small scales.

Our method allows us to model a range of plate microswimmers exhibiting different dynamics. We consider an inextensible plate ellipsoid of length L = 1, thickness h = 0.005, and variable width w, propagating bending waves along its length. Let s = [0, 1]be the length coordinate relative to the head of the swimmer in an undeformed configuration, and r = [-w/2, w/2] the width coordinate. We model planar beating in the the length x- and thickness z- plane, so that the tangent angle of the swimmer surface in this plane is

$$\psi(s,t) = As^{1/2}\cos 2\pi (ks - t),$$
(14)

giving body-frame surface coordinates

$$x = \int_0^1 \cos(\psi(s,t)) \, \mathrm{d}s, \quad z = \int_0^1 \sin(\psi(s,t)) \, \mathrm{d}s, \quad y = r,$$
(15)

and body-frame velocity

$$u = \int_0^1 -\psi \sin(\psi(s,t)) \,\mathrm{d}s, \quad w = \int_0^1 \psi \cos(\psi(s,t)) \,\mathrm{d}s, \quad v = 0.$$
(16)

This parameterisation results in the beat pattern shown in figure 6a. The two unknown swimming x and z translational velocities and the rotational velocity about the *y*-axis are found by enforcing the constraints that the swimmer is force and torque free

$$\int_{S} \mathbf{f}(\mathbf{x}, \mathbf{t}) \, \mathrm{d}S_{x} = \mathbf{0}, \quad \int_{S} \mathbf{x} \wedge \mathbf{f}(\mathbf{x}, \mathbf{t}) \, \mathrm{d}S_{x} = \mathbf{0}, \tag{17}$$

and the sheet's mean progressive velocity determined from its laboratory frame trajectory. ¹⁷

An instantaneous configuration of a swimmer with $w = 0.5, k = 5\pi/2$, and $A = \pi/3$ at time t = 0 is shown in figure 6b, together with the resultant flow streamlines, in the laboratory frame. The streamlines reveal an intricate pattern of recirculating vortices at the swimmer surface, as observed both with filament swimmers and in two-dimensional (2D) infinite sheet models; this intermediate model retains many of the flow features of both limits.

We might also ask how the mean progressive velocity of such a swimmer varies with width. Figure 6c shows the progressive velocity of this sheet swimmer as the width varies from $w = 0.3, \dots, 2$ relative to the circular disk configuration. For the range considered, slender ribbons exhibiting the same kinematics swim more quickly than broader swimmers. The hydrodynamic mechanism for this reduction for these parameters can, somewhat crudely, be understood in the following manner. The propulsive force that the sheet exerts on the fluid is approximately proportional to the area of the ellipse, which scales with w. The drag in the swimming direction can be approximated by F_{ℓ} (8). The swimming velocity is then such that drag and propulsion balance exactly, since the swimmer is force-free. However, we can observe through simple numerical evaluation of the integrals (10) that the drag force (8) increases more rapidly with width than the surface area in this régime; thus for an increase dw in width, the increase in drag dD > dF the increase in propulsion, and the swimmer moves more slowly.

It is interesting to ask if the increase in velocity continues as the width decreases further. By modelling the swimmer centreline by a line distribution of 3D regularised stokeslets, we obtained a relative swimming speed for the filament of U = 1.032. This result suggests that there may exist an optimal cross-section which produces the fastest swimming speed in the nearly filament régime (Fig. 1b) where there is currently no non-local theory, providing further motivation for its development. However, it is important to note that the regularised stokeslet slender body theory is a different method for simulating fundamentally different geometries; whilst the relative error between two RiBEM solutions for similar geometries will be small, the absolute accuracy of RiBEM is around 3% (Fig. 2), and as such further study in the nearly filament régime is required to verify the existence of this optimum.

We again note that RiBEM would be highly suited for future coupling with a shell theory that incorporates elastic bending in order to study actively bending plate swimmers, in an analoguous manner to previous work with sperm-like flagellar swimmers.³⁹

5 Discussion

We have demonstrated that the boundary element method with regularised stokeslets is an effective means of calculating the dynamics of thin ribbons and sheets, where the regularisation parameter ε is used as a proxy for the sheet thickness. Tractions are not resolved across the thickness of the sheet, but rather regularised stokeslets are distributed across a 2D manifold of the ribbon's centreline. The method is accurate in regions where asymptotic theories are not valid, and traditional boundary elements are impractical.

The method was validated against the analytical solution for the resistance matrices of various plate ellipsoids as well as previ-

(a) Magic carpet waveform



(b) Magic carpet flow



(c) Magic carpet progressive velocity



Fig. 6 (a) Grayscale time-lapse of the planar waveform of the magic carpet as defined by the tangent angle (14). (b) Flow streamlines driven by a magic carpet with $w = L/2, k = 5\pi/2$, and $A = \pi/3$ at time t = 0, demonstrating similar vortices to those observed in 2D and 3D analogues. (c) Swimming velocity of the magic carpet relative to a circular disk, demonstrating that for finite swimmers, slender filament configurations are faster than wide carpets exhibiting the same beat kinematics.

ous boundary element studies of ribbon helices, and shown to be consistent with asymptotic and boundary element studies of an experimental ribbon microswimmer. We then applied the method to study the resistance and flow surrounding a coiled section of double helix, finding that whilst the resistance matrix was very similar to an equivalent cylinder, the flow streamlines showed an interesting structure which would be important to resolve in fluidstructure interaction models. We finally examined an inextensible, finite plate microswimmer or "magic carpet", finding that for the parameters considered, making the plate wider slowed the swimmer considerably.

The diverse geometries of natural and artificial bodies that interact with microscale flows drives the need for bespoke numerical schemes that can solve hydrodynamic problems efficiently and accurately. By applying a regularised stokeslet method, we have examined the dynamics of ribbons and sheets that will be effective for a range of problems where the body thickness is much smaller than the other dimensions, and may provide a means to couple flows with plate mechanics to study fluid structure interaction problems such as the sedimention of flexible pancake-like structures, or the unfolding of chiral ribbons in ambient flow.

Acknowledgements

TDM-J is supported by a Royal Commision for the Exhibition of 1851 Research Fellowship; LK is supported by the Cambridge Trusts, Cambridge Philosophical Society and the Cambridge hardship fund; El is supported in part by the European Union through a Marie Curie CIG Grant.

References

- 1 S. Kim and S. J. Karrila, *Microhydrodynamics: Principles and Selected Applications*, Courier Corporation, 2005, p. 507.
- 2 E. Guyon, J.-P. Hulin, L. Petit and C. Mitescu, *Physical Hydrodynamics*, OUP Oxford, 2001, p. 528.
- 3 L. E. Becker, S. A. Koehler and H. A. Stone, *J. Fluid Mech.*, 2003, **490**, 15–35.
- 4 E. Lauga and T. R. Powers, *Reports Prog. Phys.*, 2009, 72, 096601.
- 5 G. K. Youngren and A. Acrivos, *Journal of Fluid Mechanics*, 1975, **69**, 377–403.
- 6 C. Pozrikidis, Boundary Integral and Singularity Methods for Linearized Viscous Flow, Cambridge University Press, 1992, p. 259.
- 7 N. Phan-Thien, T. Tran-Cong and M. Ramia, *Journal of Fluid Mechanics*, 1987, **184**, 533–549.
- 8 H. Shum, E. Gaffney and D. Smith, Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences, 2010, pp. 1725–1748.
- 9 T. D. Montenegro-Johnson and E. Lauga, *Physical Review E*, 2014, **89**, 060701.
- 10 T. D. Montenegro-Johnson, D. Gagnon, P. E. Arratia and E. Lauga, *Phys. Rev. Fluids*, 2016.
- 11 G. J. Hancock, Proc, Roy. Soc. Lond. A, 1953, pp. 96-121.
- 12 J. Gray and G. J. Hancock, J. Exp. Biol., 1955, 32, 802-814.

- 13 R. G. Cox, J. Fluid Mech., 1970, 44, 791.
- 14 G. K. Batchelor, J. Fluid Mech., 1970, 44, 419.
- 15 J. Lighthill, SIAM Rev., 1976, 18, pp. 161–230.
- 16 R. E. Johnson, J. Fluid Mech., 1979, 99, 411.
- 17 L. Koens and E. Lauga, Phys. Biol., 2014, 11, 1-15.
- 18 M. Kim and T. Powers, Phys. Rev. E, 2004, 69, 061910.
- 19 S. E. Spagnolie and E. Lauga, Phys. Fluids, 2010, 22, 031901.
- 20 S. E. Spagnolie and E. Lauga, *Phys. Rev. Lett.*, 2011, **106**, 058103.
- 21 L. Koens and E. Lauga, Phys. Fluids, 2016, 28, 013101.
- 22 L. Koens and E. Lauga, Preprint.
- 23 L. Zhang, J. J. Abbott, L. Dong, B. E. Kratochvil, D. Bell and B. J. Nelson, *Appl. Phys. Lett.*, 2009, **94**, 064107.
- 24 L. Zhang, J. J. Abbott, L. Dong, K. E. Peyer, B. E. Kratochvil, H. Zhang, C. Bergeles and B. J. Nelson, *Nano Lett.*, 2009, 9, 3663–7.
- 25 L. Zhang, K. E. Peyer and B. J. Nelson, *Lab Chip*, 2010, **10**, 2203–15.
- 26 E. Diller, J. Zhuang, G. Z. Lum, M. R. Edwards and M. Sitti, *Applied Physics Letters*, 2014, **104**, 174101.
- 27 D. J. Smith, Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences, 2009, pp. 3605–3626.
- 28 E. E. Keaveny and M. J. Shelley, J. Comput. Phys., 2011, 230, 2141–2159.
- 29 R. Cortez, L. Fauci and A. Medovikov, *Physics of Fluids (1994-present)*, 2005, **17**, 031504.
- 30 T. D. Montenegro-Johnson, S. Michelin and E. Lauga, *The European Physical Journal E*, 2015, 38, 1–7.
- 31 F. Perrin, J. Phys. Radium, 1934, 10, 497-511.
- 32 P.-O. Persson and G. Strang, SIAM review, 2004, 46, 329-345.
- 33 E. E. Keaveny, S. W. Walker and M. J. Shelley, *Nano Lett.*, 2013, **13**, 531–7.
- 34 T. Omori, H. Hosaka, Y. Imai, T. Yamaguchi and T. Ishikawa, *Physical Review E*, 2014, **89**, 013008.
- 35 S. D. Olson, S. Lim and R. Cortez, *Journal of Computational Physics*, 2013, **238**, 169–187.
- 36 G. I. Taylor, Proceedings of the Royal Society London A, 1951, 447–461.
- 37 J. R. Vélez-Cordero and E. Lauga, *Journal of Non-Newtonian Fluid Mechanics*, 2013, **199**, 37–50.
- 38 E. E. Riley and E. Lauga, *Journal of theoretical biology*, 2015, 382, 345–355.
- 39 T. D. Montenegro-Johnson, H. Gadelha and D. J. Smith, Open Science, 2015, 2, 140475.