# UNIVERSITY BIRMINGHAM University of Birmingham Research at Birmingham

# Dynamic responses of interspersed railway tracks to moving train loads

Kaewunruen, Sakdirat; Lewandrowski, Tomasz; Chamniprasart, Kritditorn

DOI: 10.1142/S0219455418500116

*License:* None: All rights reserved

Document Version Peer reviewed version

#### Citation for published version (Harvard):

Kaewunruen, S, Lewandrowski, T & Chamniprasart, K 2017, 'Dynamic responses of interspersed railway tracks to moving train loads', *International Journal of Structural Stability and Dynamics*, vol. 18, no. 1. https://doi.org/10.1142/S0219455418500116

Link to publication on Research at Birmingham portal

#### Publisher Rights Statement:

Checked for eligibility: 28/03/2017

Electronic version of an article published as Kaewunruen, Sakdirat, Tomasz Lewandrowski, and Kritditorn Chamniprasart. "Dynamic Responses of Interspersed Railway Tracks to Moving Train Loads." International Journal of Structural Stability and Dynamics (2017); https://doi.org/10.1142/S0219455418500116

© World Scientific Publishing Company - http://www.worldscientific.com/worldscinet/ijssd

#### **General rights**

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

•Users may freely distribute the URL that is used to identify this publication.

•Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.

•User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?) •Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

#### Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

# DYNAMIC RESPONSES OF INTERSPERSED RAILWAY TRACKS TO MOVING TRAIN LOADS

Sakdirat Kaewunruen<sup>\*, 1</sup>, Tomasz Lewandrowski<sup>2</sup>, Kritditorn Chamniprasart<sup>3</sup>

<sup>1</sup>School of Engineering, University of Birmingham
 <sup>2</sup>Military University of Technology in Warsaw
 <sup>3</sup>Faculty of Engineering, Chulalongkorn University

Received 23 November 2016 Accepted 27 March 2017

This paper investigates novel dynamic phenomena of interspersed railway tracks. The interspersed method is commonly carried out by spot-replacing old timber sleepers with new concrete sleepers. Although this interspersed approach provides a short-term solution, such the method has a negative effect on the long-term performance of railway tracks. It is evident that the performance of interspersed tracks can quickly deteriorate after some years. As a result, this paper is the first to evaluate dynamic responses of the interspersed track caused by a moving train load in order to understand the root cause of swift track deterioration. Interspersed track models in three-dimensional space have been developed using a finite element package, STRAND7. The model was validated earlier with experimental results. Parametric studies have been conducted to evaluate dynamic responses of the interspersed railway tracks, including dynamic displacement, frontal uplift, rear uplift and accelerations of rail over sleeper, rail at midspan, sleeper at rail seat and sleeper at midspan. Dynamic amplification phenomena are highlighted as they convey a new insight into dynamic phenomena identifying the real source of track deterioration.

**Keywords:** interspersed track, timber sleeper, concrete sleeper, moving load, envelop analysis, dynamic response, dynamic factor, nonlinear transient analysis, tensionless support.

<sup>&</sup>lt;sup>\*</sup> Corresponding author. Tel.: +44 (0) 1214 142 670

E-mail addresses: s.kaewunruen@bham.ac.uk

### **1. Introduction**

Conventional railway tracks are constructed using steel rails, sleepers, fasteners, ballast, and formation (capping layer over compacted soil). A critical review on the loading conditions acting on railway tracks for either passenger or freight trains shows that dynamic behaviour of a railway track is vital to understand the track dynamic responses to diverse loading conditions [1]. A critical loading condition, which often causes structural cracks in brittle sleepers, densifies and pulverises ballast support, is the large impact loads due to wheel/rail irregularities. For example, a common transient waveform pattern of wheel impacts due to an out-of-round wheel can be seen in Fig. 1. Clearly, the magnitude of the impact forces varies from 200kN to 400kN while the duration is ranging from 2 to 10 msec. Based on a transient pulse concept, these impact pulses are associated with the vibration excitation frequency range from 100 Hz to 500 Hz (f = 1/T: f is the frequency and T is the period). This frequency range can resonate with track components and lead to pre-mature damages. In the real world, wheel/rail interaction generates dynamic forces acting on a rail seat. The dynamic load patterns are dependent on train speed, track geometry, axle load, vehicle type, and wheel/rail defects or irregularities. Track engineers must consider the frequency ranges of static and dynamic loadings in life cycle asset maintenance and management of railway tracks with respect to critical train speeds and bespoke operational parameters [1-5].

Timber sleepers are still being used in railway track infrastructure all over the world. Their durability is estimated to be around 10 to 15 years depending on their applications, operation parameters, environmental factors and the level of maintenance quality. Partial replacement or spot replacement of timber sleepers by concrete

2

counterparts is an interesting concept to maintain track quality and improve short-term solutions that could be agile, cheap, effective and quick. This kind of spot replacement is usually adopted for the second or third class timber track or in some countries in the firstclass main line. This solution is called "interspersed track". In general, restricted train speeds are often imposed when track deteriorates to the condition below the base operation conditions (BOCs). By adopting the interspersed method, full operational speed can be allowed. Moreover, this approach strengthens for enhancement in ability to withstand high velocity operations or to restrain longitudinal rail forces preventing a track buckling [6-8]. Although partial replacement of aged, rotten sleeper is obviously highly more economical than completely track renewal or reconstruction, the interspersed track poses some disadvantages. Most often, the spot replacement concerns only on old, rotten timber sleepers and the new stiff concrete sleepers would be installed onto old and weakened foundation, which has been in services for a very long time. Moreover, the track stiffness of new track is inconsistent as the existing timber tends to be aging too. This track stiffness inconsistency and different track decay rate can be a reason of uneven settlement and foundation failure [9-13].

Owing to differential track stiffness, deterioration processes, track component durability and operational parameters, many patterns of interspersed railway tracks have been introduced i.e. 1 in 2, 1 in 3, 1 in 4 and so on (which means that there is 1 concrete sleeper in every indicated number of sleeper; for instance, 1 in 4 means 1 concrete sleeper in every 4 sleepers including the concrete itself). This type of railway track mainly exists in a rail network with low operational speeds. A key reason is that this type of track has various flaws derived from how it is built. These can impair the long-term performance

of interspersed railway tracks as shown in Figure 1 [13]. Figure 1 shows the conditions of interspersed railway tracks in low-speed operation (<25 km/h). The tracks have been commissioned between 2006 and 2008 and have served as a main high-speed link to maintenance junctions. The photos were taken in April 2016 during a site visit.

The serviceability limit state of the railway track has become the governing criteria for sleepers made of different material properties in the existing aged track systems. It is important to note that a general recommendation (e.g. by Australian Office of Transport Safety Investigations) is to perform concrete sleeper installation only 'inface' (i.e. the practice of installing the same sleeper type continuously rather than interspersed with other sleepers in between, also referred to as 'on-face') [11-13]. This paper aims at investigating the dynamic responses of the interspersed railway tracks to a moving train envelope. Based on critical literature review, this research has never been presented in open literature [14-21]. A class of two-dimensional interspersed track models was created using Timoshenko beams in a finite element package, STRAND7. Dynamic displacement, frontal uplift, back uplift and accelerations have been evaluated at rail over sleeper, rail at midspan, sleeper at rail seat and sleeper at midspan. Dynamic amplification phenomena are then highlighted in this paper. The insight into the interspersed track responses will help rail track engineers to enable a truly predictive maintenance and improve the reliability of infrastructure asset maintenance and management.

#### 2. Track model

A two-dimensional Timoshenko beam model was previously developed and found to be one of the most suitable options for modeling concrete sleepers [22-25]. In this study, the

finite element models of railway tracks have been developed and calibrated against the numerical and experimental modal parameters [25-27]. Figure 2 shows the finite element models in three-dimensional space for an in-situ railway track with different types of sleepers. Using a general-purpose finite element package STRAND7 [28], the numerical model included the beam elements, which take into account shear and flexural deformations, for modeling the sleeper and rails. Each sleeper consists of 60 beam elements and each rail consists of 200 beam elements. The 60kg rail cross section and sectional parameters (Area: 17,789.9 mm<sup>2</sup>; Second moment of Area: 43.2 x10<sup>6</sup> mm<sup>4</sup>) were used in accordance with Australian Standard AS1085.1 [29]. The trapezoidal crosssection was assigned to the concrete sleeper elements in accordance with the standard medium duty sleepers (204 mm top-wide x 250 mm bottom-wide x 180 mm deep) [30-31]. The rectangular cross-section was assigned to the timber sleeper elements in accordance with the standard timber sleepers (230 mm wide x 130 mm deep) used in NSW [32]. The rail pads at railseats were simulated using a series of spring-dashpot elements. The distance offset between rails and sleepers was set to 100mm to more clearly illustrate the track behaviours. This setup does not affect the numerical results [27-28]. In this study, the stiffness and damping values of high density polyethylene (HDPE) pads were assigned to these spring-dashpot elements [26]. The support condition was simulated using the nonlinear tensionless beam support feature in STRAND7 [28]. This attribute allows the beam to lift over the support while the tensile supporting stiffness is omitted. The tensionless support option can correctly represent the ballast characteristics in real tracks [27-28]. The sleepers are connected to both rails using spring-dashpot elements with hinge nodes at railseats. The displacement restraints have

been applied to the rail ends. The experimental modal testing was first performed to identify structural parameters of the sleepers. Then, the finite element model was developed using available data from the manufacturer. The model was then updated through the comparison of modal parameters. Table 1 shows the geometrical and material properties of the finite element model. Based on previous studies [20-27], effects of length and boundary of track in this study (18 bays or 10.8 m) on the computation and the frequencies of interest are negligible. These data have been validated and the verification results were presented elsewhere [27].

In total, 5 types of interspersed tracks have been established for dynamic investigations, including pure concrete, pure timber, 1 in 2, 1 in 3 and 1 in 4. The '1 in 2' means concrete and timber sleeper placed alternately. The '1 in 3' implies that one concrete sleeper installed in two adjacent timber sleepers, and the '1 in 4' means one concrete sleeper installed with three adjacent time sleepers. All types of track are shown in Figures 2. Engineering properties of each element are tabulated in Tables 1 - 5. All dimensions are given in millimeters. The partial support condition, which has been reported to be more suitable for standard gauge tracks [30], has been adopted for this study (as illustrated in Figure 2f). Spring – dashpot model of rail pad is presented in Figure 2g. For the envelope study, four separated forces with a constant magnitude of 100kN have been used to imitate the loading condition of a passenger train bogie (2 per each rail, 2 meters apart). This load magnitude has been used for benchmarking purpose [33-36]. The non-dimensional analyses have then been carried out to investigate the dynamic amplification over train speed and over frequency domain.

### 3. Results

The Linear Static Solver of Strand 7 has been used to solve for the static behavior of railway tracks. For the static analysis, the position of axle loads coincides with the axle of the model. The Nonlinear Transient Solver is then used to solve the dynamic cases. For the dynamic analysis two load paths with the moving load envelope have been established. The dynamic analyses are been conducted for a range of train speeds from 10km/h to 120km/h with a step of 10km/h. To appropriately take into account the moving loads, the analysis duration (iteration time steps) has been set adaptively in order to enable entire load pass-bys in the models. Table 6 displays the time steps of calculations in each case. Vertical track displacements, front and back uplifts and dynamic accelerations of the track are investigated under both the static and the moving load conditions. The emphasis of these numerical simulations is placed on the dynamic responses at critical locations, including rail over sleeper, rail at midspan, sleeper under rail and sleeper at midspan. Dynamic amplification factors are calculated as a ratio of dynamic over static response. Typical dynamic deformation of a railway track under the moving load can be demonstrated in Figure 3. It can be observed that right under the trainload, the rails and sleepers flex due to positive bending whilst there exist uplift actions in front of and at rear of the bogie load. The front and back (or rear) uplifts of rails can be noticed in all dynamic simulation cases. In addition, when the load moves pass by a position, all numerical simulations reveal that the rail uplifts excite the sleepers upward and also result in amplified vertical vibrations and uplift displacements of railway sleepers. The sagging and hogging behaviors of sleeper component could then be pronounced by the dynamic responses of interspersed tracks.

Figure 4 demonstrates the dynamic effects of interspersing methods coupled with train speeds on the maximum displacement responses of rails and sleepers. Considering the rail responses over the sleepers, it is clear that timber sleepered tracks deform vertically higher than interspersed or concrete sleepered tracks. The timber sleepered tracks tend to resonate with the train speeds from 90 to 100 km/h. On the other hand, concrete sleepered tracks seem to resonate with the train speed of around 70 km/h. Based on the front uplift of rails, it can be observed that the interspersed track poses a significantly larger upward displacements, in comparison with either timber or concrete sleepered tracks. On average, timber sleepers in the interspersed tracks displace at larger amplitude compared with concrete counterparts. This implies a considerable pulverization and densification of ballast and supporting formation under timber sleeper zone from the train pass-bys. This damage has in fact been evident from the site visit where track mud pumping (formation stress failure) has been observed right under timber sleepers in the interspersed tracks muder timber sleepers in the interspersed tracks where track muder tracks.

In addition, when consider the dynamic responses of sleeper at mid span, inverse behavior can be observed. The concrete sleepers in the 1:4 interspersed tracks hog largely under the moving loads compared with other sleepers. This could induce ballast dilation and cause center-bound failure in the future. Also, it can be seen that the timber's elasticity has yielded well stress redistribution along the sleeper, resulting in less hogging behavior of the timber sleepers.

Accelerances of rails and sleepers have been evaluated as shown in Figure 5. It can be found that rails, at both over sleeper and in between sleepers, in the concrete sleepered track vibrate at the lowest amplitude of acceleration. This is because concrete sleepers usually have higher mass that could pin down the rails and inversely proportionate to accelerations. It is noted that the level of accelerance of rails of interspersed and timber sleepered tracks is significantly higher than that of concrete sleepered tracks. However, it can be observed that timber component poses an antiresonance associated with a train speed of 90 km/h. In addition, the accelerations of sleepers at rail seat and at mid span clearly demonstrate a similar trend. The timber sleepers tend to accelerate faster and greater due to its light weight. This causes enduring track vibrations and triggers systems oscillations. This dynamic behavior coincides with the observed location where ballast dilates or spreads out around the edge of sleepers, especially around concrete sleepers in the interspersed tracks. Without appropriate track maintenance, ballast dilation can undermine such the location that the track section loses lateral resistance and will be prone to track buckling under extreme heat condition.

Dynamic amplification factors of rails and sleepers are illustrated in Figure 6. It clearly shows that concrete has poor performance in dampening rail vibration responses. However, higher concrete density helps to stabilise railway tracks by reducing uplift dynamics of the rail over the sleepers and of the rail at mid span. When consider the sleepers at rail seat (sleeper under rail), the interspersed track could better provide anti-resonant mechanism that counter balance the dynamic amplification by its unbalanced mass systems (different sleeper masses). However, the anti-resonant benefit could appear only for the vertical downward responses. It is found from all cases that the very

dominant uplift responses of all sleepers in the interspersed tracks are highly likely to induce damages on track components due to their ability to amplify the sleeper uplift responses at the railseats. Similar trend can also be observed on the dynamic responses of the sleepers at mid span. However, it should be noted that the concrete sleeper in '1 in 4' interspersed track suffers the most from negative bending moment, which could later cause center-bound problem (where sleeper flex upward and cracks develop from the top surface).

#### 4. Conclusion

Interspersed tracks where spot replacement of sleeper exists can still be found in many countries around the world. Such practice can cause excessive track maintenance over time. This is because a cluster of timber sleepers with mixed quality could deteriorate faster than the others and the replacement by concrete sleepers could induce track stiffness inconsistency and aggravate loading conditions acting on the track. This paper is found to be the first to investigate dynamic responses of the interspersed track caused by a moving train load in order to understand the root cause of rapid track deterioration. A finite track models in three-dimensional space have been established and validated. The parametric studies have revealed the key insights into the actual source of track deterioration, including:

#### Rails

Maximum displacements of the rail are the smallest in the concrete sleepered tracks. However dynamic amplification factor is the greatest for this type of track. On the other hand, dynamic uplift amplification factor is the lowest in the concrete sleepered track due

10

to its higher density. In timber and interspersed tracks, the uplift responses of rails can be pronounced and considered as the key source that triggers other mode of track vibrations, which could induce ballast pulverization, ballast dilation, and uneven densification.

#### Sleepers

Maximum displacement responses of the sleeper at railseat are smallest in the concrete sleepered tracks. However, it is found that dynamic amplification factors in these cases are the largest. Dynamic uplifts of sleeper at railseat in interspersed tracks can be significantly amplified especially for the concrete sleepers. Similar trend can also be observed for the mid span of concrete sleepers. Importantly, it is clear that the timber sleepers in the '1 in 3' and '1 in 4' interspersed tracks suffer exceptionally from the moving train loads. Not only can the dynamic uplift of the timber sleepers break ballast gravels, but it can also induce additional magnitude of stress wave onto formation and result in formation failure. This is evident from the actual field inspection where mud pumping often initiates under the timber sleepers in the interspersed tracks.

#### Acknowledgements

The authors are grateful for the financial sponsorships to Japan Society for the Promotion of Science (JSPS) via Grant No. JSPS-L15701, BRIDGE Grant (Collaboration between University of Birmingham and University of Illinois at Urbana Champaign), and European Commission for H2020-MSCA-RISE Project No. 691135 "RISEN: Rail Infrastructure Systems Engineering Network", which enables a global research network that tackles the grand challenge in railway infrastructure resilience and advanced sensing in extreme conditions (www.risen2rail.eu). The valuable discussions and comments from

ISO/BSI standard committee for railway sleepers (TC269 WG7 chaired by Dr Makoto Ishida and BSI WG by Neil Gofton) are gratefully acknowledged.

### References

- 1. A.M. Remennikov, S. Kaewunruen, A review on loading conditions for railway track structures due to wheel and rail vertical interactions. *Structural Control and Health Monitoring*, 15(2) (2008) 207-234.
- A.M. Remennikov, S. Kaewunruen, Determination of dynamic properties of rail pads using instrumented hammer impact technique, *Acoustics Australia*, 33(2) (2005) 63-67.
- S. Kaewunruen, A.M. Remennikov, Influence of ballast conditions on flexural responses of railway concrete sleepers, *Concrete in Australia: Journal of Concrete Institute of Australia* 35(4) (2009) 57-62.
- S. Kaewunruen, A.M. Remennikov, Dynamic properties of railway track and its components: Recent finding and future research directions. *Insight - Non-Destructive Testing and Condition Monitoring*, 52(1) (2010) 20-22.
- S. Kaewunruen, A.M. Remennikov, A. Akira, S. Hirotaka, Free vibrations of interspersed railway track systems in three-dimensional space. *Acoustics Australia*, 42(1) (2014) 20- 26.
- Z. Cai, Modelling of rail track dynamics and wheel/rail interaction, *Ph.D. Thesis*, Department of Civil Engineering, Queen's University, Ontario, Canada, (1992).
- S. Kaewunruen, A.M. Remennikov, Effect of improper ballast packing/tamping on dynamic behaviours of on-track railway concrete sleeper, *International Journal of Structural Stability and Dynamics* 7(1) (2007) 167-177.
- R. Gustavson, Structural behaviour of concrete railway sleepers, *Ph.D. Thesis*, Department of Structural Engineering, Chalmers University of Technology, Sweden, (2002).
- 10. R. Kohoutek, Dynamic and static performance of interspersed railway track, *Proceedings of Conference on Railway Engineering*, Vol 1, pp.153-159 (1991).

- 11. M. Lake, L. Ferreira, M.H. Murray, Using simulation to evaluate rail sleeper replacement alternatives, *Transportation Research Record*, 1785 (2002) 58-63.
- S. Kaewunruen, S. Mimoura, T. Watanabe, A.M. Remennikov, Remaining service life of railway prestressed concrete sleepers, *International RILEM Conference on Materials, Systems and Structures in Civil Engineering*, DTU, Denmark, 10p (2016).
- S. Kaewunruen, K. Chamniprasart, Damage analysis of spot replacement sleepers interspersed in ballasted railway tracks, *Proceedings of the 29<sup>th</sup> Nordic Seminar on Computational Mechanics*, October 2016, Chalmers University of Technology, Sweden (2016).
- S. Kaewunruen, A.M. Remennikov, Sensitivity analysis of free vibration characteristics of an in-situ railway concrete sleeper to variations of rail pad parameters, *Journal of Sound and Vibration* 298(1-2) (2006) 453-461.
- S. Kaewunruen, A.M. Remennikov, Dynamic flexural influence on railway concrete sleepers in track systems of a wheel impact. *Engineering Failure Analysis*, 16(3) (2009) 705-712.
- S. Kaewunruen, A.M. Remennikov, Impact capacity of railway prestressed concrete sleepers. *Engineering Failure Analysis*, 16(5) (2009) 1520-1532.
- S. Kaewunruen, A.M. Remennikov, Investigation of free vibrations of voided concrete sleepers in railway track system, *Proceedings of the Institution of Mechanical Engineers Part F Journal of Rail and Rapid Transit*, 221(4) (2007) 495-508.
- J. Sadeghi, Investigation of characteristics and modeling of railway track system, *PhD Thesis*, University of Wollongong, Australia (1997).
- 19. D.J. Thompson, *Railway Noise and Vibration*. Elsevier, Amsterdam, The Netherlands (2010).
- S. Kaewunruen, A.M. Remennikov, Nonlinear transient analysis of railway concrete sleepers in track systems. *International Journal of Structural Stability and Dynamics*, 8(3) (2008) 505-520.

- S. Kaewunruen, A.M. Remennikov, Dynamic crack propagations of prestressed concrete sleepers in railway track systems subjected to severe impact loads. ASCE Journal of Structural Engineering, 136(6) (2010) 749-754.
- S. Kaewunruen, A.M. Remennikov, Effect of a large asymmetrical wheel burden on flexural response and failure of railway concrete sleepers in track systems, *Engineering Failure Analysis*, 15(8) (2008) 1065-1075.
- 23. S. Grassie, *Dynamic modelling of concrete railway sleepers*. Journal of Sound Vibration, 187 (1995) 799-813.
- 24. J. Neilsen, *Eigenfrequencies and eigenmodes of beam structures on an elastic foundation*. Journal of Sound and Vibration, 145 (1991) 479-487.
- S. Kaewunruen, A.M. Remennikov, Experimental simulation of the railway ballast by resilient materials and its verification by modal testing, *Experimental Techniques*, 32(4) (2008) 29-35.
- S. Kaewunruen, A.M. Remennikov, An alternative rail pad tester for measuring dynamic rail pad properties under large preloads, *Experimental Mechanics*, 48(1) (2008) 55-64.
- S. Kaewunruen, A.M. Remennikov, Application of vibration measurements and finite model updating for structural health monitoring of ballasted railtrack sleepers with voids and pockets. Book Chapter in Sapri, R.C. (ed), Mechanical Vibration, Nova Science Publishers, New York, pp. 621-644 (2009).
- 28. G+D Computing, Using Strand7: Introduction to the Strand7 finite element analysis system, Sydney, Australia, (2001).
- 29. Standards Australia, AS1085.1 Rail, Sydney, Australia (2001).
- Standards Australia, Australian Standard: AS1085.14-2003 Railway track material -Part 14: Prestressed concrete sleepers, Sydney, Australia (2003).
- RailCorp, Engineering Specification SPC233 Concrete sleepers and bearers, Sydney, Australia (2013).
- RailCorp, Engineering Specification SPC231 Timber sleepers and bearers, Sydney, Australia (2013).

- O. Mirza, S. Kaewunruen, D. Galia, Seismic vulnerability analysis of Bankstown's West Terrace railway bridge, *Structural Engineering and Mechanics, An International Journal* 57 (3) (2016) 569-585.
- S.L. Binti Sa'adin, S. Kaewunruen, D. Jaroszweski, Operational readiness for climate change of Malaysia high-speed rail, *Proceedings of the Institution of Civil Engineers-Transport* 169 (5) (2016) 308-320.
- 35. E.K. Gamage, S. Kaewunruen, A.M. Remennikov, T. Ishida, Toughness of Railroad Concrete Crossties with Holes and Web Openings. *Infrastructures* (2017), 2, 3.
- E.K. Gamage, S. Kaewunruen, A.M. Remennikov, T. Ishida, Reply to comment 'Toughness of Railroad Concrete Crossties with Holes and Web Openings'. *Infrastructures* (2017), in press.

Parameter lists		
Length	$l_r = 10.8$	m
Gauge	g=1.5	m
Modulus	$E_r = 2.0000e5$	MPa
Poisson's ratio	v <sub>r</sub> =0.25	-
Density	d <sub>r</sub> =7850	kg/m <sup>3</sup>

**Table 1** Engineering properties of rail used in the modeling

# **Table 2** Engineering properties of rail pad used in the modeling

Parameter lists		
Rail pad stiffness	$k_{p} = 17$	MN/m

# **Table 3** Engineering properties of concrete sleeper used in the modeling

Parameter lists		
Length	$l_{\rm s}=2.5$	m
Spacing	s=0.6	m
Modulus	$E_s = 3.7451e4$	MPa
Shear modulus	$G_s = 1.0896e4$	MPa
Density	$d_s = 2740$	kg/m <sup>3</sup>

## **Table 4** Engineering properties of timber sleeper used in the modeling

Parameter lists		
Length	lt=2.5	m
Spacing	s=0.6	m
Modulus	$E_t = 1.2300e4$	MPa
Poisson's ratio	$v_t = 0.00$	-
Density	d <sub>t</sub> =1250	kg/m <sup>3</sup>

**Table 5** Engineering properties of concrete sleeper used in the modeling

Parameter lists		
Ballast stiffness	$k_{b} = 13$	MPa

V [km/h]	TOTAL STEPS	TIME STEP [s]	TIME [s]
10	5250	0,001	5,250
20	3250	0,001	3,250
30	2250	0,001	2,250
40	1500	0,001	1,500
50	1250	0,001	1,250
60	1000	0,001	1,000
70	1000	0,001	1,000
80	1000	0,001	1,000
90	1000	0,001	1,000
100	1000	0,001	1,000
110	1000	0,001	1,000
120	1000	0,001	1,000

 Table 6 Time of calculation for Nonlinear Transient Solver



Figure 1: Deteriorated interspersed railway track (a) Top: mud pumping,

and (b) Bottom: ballast pulverisation and ballast dilation



**d**) The model of 1 in 3 track



e) The model of 1 in 4 track



**f**) The support of sleepers



g) Spring – dashpot model of rail pad

Figure 2 Dynamic track models



Fig. 3 The example of the track's deformation under the moving load



a) Maximum displacement of rail over sleeper



**b**) Maximum displacement of rail at midspan



c) Maximum front uplift of rail over sleeper



d) Maximum front uplift of rail at midspan



**f**) Maximum front uplift of sleeper under rail

SPEED [km/h]

0,00



g) Maximum back uplift of sleeper under rail





i) Maximum front uplift of sleeper at midspan



j) Maximum back uplift of sleeper at midspan

Fig. 4 Displacement responses of railway tracks under the moving load



a) Maximum acceleration of rail over sleeper



**b**) Maximum acceleration of rail at midspan



c) Maximum acceleration of sleeper under rail



d) Maximum acceleration of sleeper at midspan

Fig. 5 Acceleration responses of railway tracks under the moving load



a) Dynamic factor – rail over sleeper – displacement







d) Dynamic factor - rail at midspan - displacement







g) Dynamic factor of sleeper under rail



i) Dynamic factor – sleeper under rail – back uplift



j) Dynamic factor of sleeper at midspan



l) Dynamic factor – sleeper at midspan – back uplift **Fig. 6** Dynamic amplification phenomena of railway tracks under moving load