

# Cascading effects on Overhead Line Equipment (OHLE) of extreme wind and flood events

Ngamkhanong, Chayut; Kaewunruen, Sakdirat; Baniotopoulos, Charalampos

*License:*

None: All rights reserved

*Document Version*

Peer reviewed version

*Citation for published version (Harvard):*

Ngamkhanong, C, Kaewunruen, S & Baniotopoulos, C 2019, Cascading effects on Overhead Line Equipment (OHLE) of extreme wind and flood events. in *Dealing with Disasters, GCRF, UK Alliance for Disaster Research, Disasters Research Group and UK Collaborative for Development Research: DwD-UKADR-DRG-UKCDR, International Conference, 2019*. Northumbria University, pp. 17-17, DwD-UKADR-DRG-UKCDR, International Conference 2019, Newcastle, United Kingdom, 17/07/19. <<https://northumbria-cdn.azureedge.net/-/media/corporate-website/new-sitecore-gallery/events/dwd-gcrf-ukadr-drg-ukcdr-presentation-abstracts-2019.pdf?modified=20190718092137&la=en&hash=E4ECB5043CB01B41927FABB458695292C07275FD>>

[Link to publication on Research at Birmingham portal](#)

**Publisher Rights Statement:**

Checked for eligibility: 29/07/2019

**General rights**

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

**Take down policy**

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact [UBIRA@lists.bham.ac.uk](mailto:UBIRA@lists.bham.ac.uk) providing details and we will remove access to the work immediately and investigate.

# **Cascading effects on Overhead Line Equipment (OHLE) of extreme wind and flood events**

Chayut Ngamkhanong

School of Engineering, University of Birmingham, Birmingham, UK

[cxn649@student.bham.ac.uk](mailto:cxn649@student.bham.ac.uk)

Sakdirat Kaewunruen

School of Engineering, University of Birmingham, Birmingham, UK

[s.kaewunruen@bham.ac.uk](mailto:s.kaewunruen@bham.ac.uk)

Charalampos Baniotopoulos

School of Engineering, University of Birmingham, Birmingham, UK

[c.baniotopoulos@bham.ac.uk](mailto:c.baniotopoulos@bham.ac.uk)

## **Abstract**

In modern railway systems, overhead line equipment (OHLE) is the component for the electric train which provides electric power to the train. Due to its slenderness, cantilever mast, which supports the OHLE for one or two tracks, is one of the vulnerable components in railway system. Note that, as previously recorded, the strong wind caused considerable damage over the large area and possibly cause electricity failures on OHLE. According to previous studies, it was found that OHLE can be failed due to the large contact wire displacement caused by earthquake and ground borne vibrations. This study presents the cascading effects of extreme wind and flood events on OHLE. It is interesting to note that flood event may undermine the bearing capacity led to improper support conditions and its foundation resulting in soil stiffness reduction. Finite element model updating technique has been used to perform the dynamic responses of OHLE considering soil-structure interaction of OHLE subjected to extreme winds. The scaled winds at various magnitudes are applied to the OHLE. It is interesting that the flood event plays a significant role in the dynamic responses of OHLE by reducing its support stiffness. Moreover, strong wind together with flood event can easily cause damage to OHLE. The obtained results demonstrate that the extreme wind and flood events can significantly cause catastrophic damage to the OHLE which linked to the failure of electric train. The insight will raise the awareness of engineers for better design of cantilever mast structure and its support condition for future natural hazards.