

Viaduct maintenance for future traffic demands and earthquakes

Omura, Takashi; Kaewunruen, Sakdirat

DOI:
[10.1680/jinam.19.00063](https://doi.org/10.1680/jinam.19.00063)

License:
None: All rights reserved

Document Version
Peer reviewed version

Citation for published version (Harvard):
Omura, T & Kaewunruen, S 2020, 'Viaduct maintenance for future traffic demands and earthquakes', *Infrastructure Asset Management*. <https://doi.org/10.1680/jinam.19.00063>

[Link to publication on Research at Birmingham portal](#)

General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

Template for engineering journal articles

- Date text written and revised: August 2019
 - Number of words: 4992 words
 - Number of figures: 12 figures
 - Number of tables: 9 tables
-

Title (94 characters, including spaces)

Econometric analysis of viaducts maintenance considering future traffic demand and earthquakes

Author 1

- Takashi Omura, MEng, MSc
- Department of Civil Engineering, University of Birmingham, Birmingham, United Kingdom
- ORCID number 0000-0003-4313-5928

Author 2

- Sakdirat Kaewunruen, PhD
- School of Civil Engineering Birmingham Centre for Railway Research and Education, University of Birmingham, Birmingham, United Kingdom
- ORCID number 0000-0003-2153-3538

Full contact details of corresponding author

- Sakdirat Kaewunruen
- Contact address: Edgbaston Birmingham B15 2TT United Kingdom
- Email: s.kaewunruen@bham.ac.uk

Abstract

Tokyo Metropolitan Expressway has operated for more than half a century. Recently, serious damages in the network have been reported in many of the old routes. In contrast, the Metropolitan Expressway has little to none of experience in managing such a situation so far. Thus, developing an appropriate management strategy focusing around maintenance is critical to the Expressway. The emphasis of this study is placed on the maintenance improvement of steel viaducts and the project aims to evaluate its marginal maintenance cost and identify the influences on the cost from uncertainties such as earthquakes and future traffic demand from an econometric perspective. The study reveals that the traffic volume of passenger cars can be identified as a significant factor although the effect of earthquake events on the cost is not clearly pronounced. Based on the analyses, it is found that the current maintenance approach is capable of dealing with fluctuation of traffic volume, which is the most influential factor. Furthermore, an increase in the amount of maintenance works could possibly lower the maintenance costs due to the existence of economy of scale. The results also indicate that the efficiency of current maintenance method could be improved.

Keywords chosen from ICE Publishing list

Roads & highways; Viaducts; Economics & finance; Maintenance & inspection

List of notation

AADT – Annual Average Daily Traffic volume

RTS – Returns To Scale

SUR model – Seemingly Unrelated to the Regression model

FGLS estimation – Feasible Generalized Least Squares estimation

1 Introduction

Tokyo Metropolitan Expressway Company Limited (MECL) has been established in 1959 for the purpose of reducing traffic congestion in and around Tokyo. Recently, deterioration and various kinds of damage have become prominent in its structures especially in the old expressway network. Furthermore, most of the Metropolitan Expressway consists of bridges, tunnels and semi-underground structures (Metropolitan Expressway Company Limited, 2015). Thus, it is highly important to understand maintenance costs in the structures in terms of traffic volume.

Link (2005 and 2014) analysed highway maintenance costs from an econometric viewpoint. However, he focused only on highways which consist of embankments. Hence, this study focused on maintenance costs in a steel structure which is one of the main structures in the Metropolitan Expressway shown in Figure 1 and derived the maintenance marginal cost in consideration of the influence of traffic volume. In fact, MECL needs to have its own standard to judge the best maintenance method depending on the structural damage such as general repair or structural renewal need to be established. Metropolitan Expressway Route 3 Shibuya Line ("Route 3"), which is one of the oldest expressways constructed in 1967, was focused. Especially in such old expressways, the suitable maintenance standard is assumed to be significantly important. Moreover, there have been many earthquakes and they have had large negative effects on many structures in Japan (Heath, 1995). Although it is difficult to predict earthquakes precisely, their influences on the maintenance cost should be considered. Therefore, an analysis of the effects of earthquakes as well as the effects by traffic volume was implemented. This study will play a role to judge more suitable maintenance method in consideration of future traffic volume and earthquakes.

The aim of this study is to identify the influence on the maintenance cost for a steel viaduct in Route 3 from uncertainties such as earthquakes and future traffic volume and the cost efficiency of the current maintenance method.

2. Literature review

Many economic approaches with various functions have been taken to express behaviours of producers in the past (Ferrier and Lovell, 1990 and Podolny 1993). These approaches can generally be divided into two parts. The first aims to estimate the largest profits by the use of a production function (Fare, Grosskopf and Pasurka, 2007). The other is to identify an optimal marginal cost by using a cost function. The marginal cost estimation has been conducted in various business sectors such as power generation, water utility, bus management, banking and agricultural industries (Atkinson and Halvorsen, 1984, Bottasso and Conti, 2009, Mizutani and Urakami, 1999, Viton, 1981 and Coelli, 1995). Cost functions used in past studies can be divided into two groups. The first group is a function, which has no theoretical economic background (Ford and Warford, 1969, Mann and Mikesell, 1976 and Morgan, 1977). The other is a function based on the economic corporate behaviour principle, where any enterprise seeks to minimise cost of input factors under production cost as a key criterion (Feigenbaum and Teeples, 1983, Pulley and Braunstein, 1992 and Kim, 1987). In the former, cost is regarded as explained variable and the factors considered to influence on the cost is regarded as an explanatory variable. In the latter, a cost function with an economic theoretical background expresses a mathematical formula between the cost, production output and input factor, which is demonstrated in Equation (3).

Moving on to cost function models, four types of cost function models such as linear, log linear, Cobb-Douglas and translog models were used in previous research. Linear and log linear cost function models have no theoretical economic background. On the other hand, other two types of cost function models such as Cobb-Douglas and translog models are based on theoretical economic background. Particularly, the translog cost function model introduced by Christensen, Jorgenson and Lau (1973) is more flexible than Cobb-Douglas model in terms of having the ability to deal with changeable elasticity of substitution. Thus, it can be assumed that the translog cost function model express the minimum cost of production more precisely than other models. Clark and Speaker (1994) calculated scale of economy in the banking business by use of a translog cost function. As for scale of economy, Deller, Chicoine and Walzer (1988) researched whether introduction of larger units could achieve cost saving in consideration of rural road management.

61
62 Recently, as for highway management, Link (2006) analysed renewal marginal cost in German
63 highways and the relationship between traffic volume and the renewal cost by using the translog
64 cost function. Furthermore, Link (2014) analysed the relationship between traffic volume and
65 maintenance cost, and calculated the cost elasticity and the marginal maintenance cost for
66 pricing determination. As a result of the research, a decreasing elasticity curve and decreasing
67 marginal cost curve could be derived. Moreover, the research also provided evidence for price-
68 inelastic factor and existence of returns to scale in the course of road maintenance. As
69 described above, the translog approaches have been adopted to evaluate various kinds of
70 public infrastructure industry. Meanwhile, MECL which runs the Metropolitan Expressway has
71 consistently managed the expressway and has attached the heaviest weight to achieving the
72 highest user convenience at a minimal cost since its establishment (Metropolitan Expressway
73 Company Limited, 2017a). In other words, the company has not always run its expressway to
74 maximise its profit margin as its focus is the public good. Hence, using a translog approach
75 which is appropriate for deriving cost minimising behaviour is assumed to fit the corporate
76 mission. Furthermore, it should be crucial for the company which owns various kinds of roads to
77 understand their optimal maintenance cost and the factor with uncertainty which influences
78 positive and negative impact on them. Thus, this study analysed optimal maintenance cost and
79 the influential factors in a steel road structure nobody has ever tackled.

81 **3. Maintenance methods for the Metropolitan Expressway**

82 Since the total length of Metropolitan Expressway is more than 300km and its structure types
83 have gradually become diverse since it opened, MECL created an inspectional manual for
84 maintaining the expressway. In addition to that, MECL has undertaken effective and timely
85 renewal of the manual. The manual shows the flow of inspection, the type of inspection
86 depending on the purpose and the situation, the method, required skills and qualifications for a
87 maintenance engineer and the standard for inspectional results. The criteria to judge the
88 necessity of maintenance is quite important among it. When structures are inspected, the spots
89 are classified according to 4 grades of seriousness listed in Table 1. Fundamentally, serious
90 damage classified as rank A or B are regarded as needing to be repaired in the maintenance

strategy. Therefore, maintenance costs analysed in this study are caused by the maintenance works for damage classified as rank A and B. Furthermore, the manual evaluates grades of damages in consideration of the effects on the performance required for a structure. As Table 2 shows, the performance can be categorised into “safety”, “usability” and “sociality”. Although safety and usability are obviously important, MECL regards sociality to be as important as other two performances. Note that “Sociality” means harmony of the expressway and the environment along it in terms of its appearance, noise, vibration and so on. The Metropolitan Expressway exists almost solely in the most densely populated areas in Japan. Therefore, the way of grading damage is assumed to be focused more on sociality than other Japanese roads.

4. Methodology

4.1 Translog cost function method

As mentioned before, many scholars have used economic approaches such as cost functions to identify relationships between cost, output and factor of production. In addition, Coelli (1995) stated a cost function can represent a minimum cost from a given series of inputs, whereas a production function can represent maximum output. Since MECL considers minimum-cost management as a corporate mission, this study also aims to identify a minimum operational cost. Specifically, a translog cost function was used to analyse the relationship between maintenance cost, traffic volume as an output, and maintenance marginal cost for a criterion to introduce a feasible maintenance plan. The analysis period was 10 years between 01/04/2007 and 31/03/2016. Characteristically, annual average daily traffic volume (“AADT”) of passenger and large-sized cars were used as a main explanatory variable. Earthquake frequency was also used as an explanatory variable. Furthermore, labour cost, material and machinery cost (“material cost”), and capital cost are necessary to implement expressway maintenance and are considered as factors of production. The damage which needs maintenance works is assumed to be reflected in levels of maintenance costs.

The meaning and derivation of a translog cost function are explained as follows. First, when x_i is factors of production and output Y is an input of factors of production, a production function can be shown below.

$$Y = f(x_1, x_2, x_3, \dots)$$

x_i ; factors of production

(1)

A cost function can be illustrated as a formula (2) because a production function and a cost function have antipodal relationship each other.

$$Cost = g(Y_1, Y_2, \dots, P_1, P_2, P_3, \dots)$$

Y_i : Economic goods as an output, P_j : price of factors (of production)

(2)

When a formula (2) is logarithmic transformed and applied to Taylor's expansion, formula (3) can be obtained.

$$\begin{aligned} \ln Cost = \alpha_0 + \sum_i \beta_i \ln P_i + \frac{1}{2} \sum_i \sum_j \beta_{ij} \ln P_i \ln P_j + \sum_l \gamma_l \ln Y_l + \frac{1}{2} \sum_l \sum_m \delta_{lm} \ln Y_l \ln Y_m \\ + \sum_i \sum_l \rho_{il} \ln P_i \ln Y_l \end{aligned}$$

(3)

In this study, expressway viaducts focused on were made of steel and constructed in 1967. AADT of passenger and large-sized cars were denoted by Y_p and Y_f as produced economic output. Moreover, if labour cost P_L , material cost P_M and capital cost P_C are defined as factors of production, a cost function can be shown below. Capital cost P_C is regarded as depreciation cost which annually needs to be paid depending on the size of the expressway asset value.

142

$$Cost = f(Y_p, Y_f, P_L, P_M, P_C)$$

143

(4)

144

145 In addition, higher earthquake frequencies tend to increase maintenance cost and was added
 146 as a dummy variable N to a constant term which illustrates environmental condition in the
 147 expressway structure. The essential conditions for homogeneity in price of factors and for
 148 symmetry can be illustrated below (Link, 2006).

149

$$\sum_i \beta_i = 1, \sum_j \beta_{ij} = 0, \sum_i \rho_{il} = 0, \beta_{ij} = \beta_{ji}$$

150

(5)

151

152 Based on this explanation above, the translog cost function used in this study can be exhibited
 153 below.

154

$$\begin{aligned} \ln Cost = & c + \alpha \cdot \ln N + \beta_L \ln P_L + \beta_M \ln P_M + \beta_C \ln P_C + \gamma_p \ln Y_p + \gamma_f \ln Y_f \\ & + \frac{1}{2} (\beta_{LL} \ln^2 P_L + \beta_{MM} \ln^2 P_M + \beta_{CC} \ln^2 P_C + \delta_{pp} \ln^2 Y_p + \delta_{ff} \ln^2 Y_f) + \beta_{LM} \ln P_L \ln P_M \\ & + \beta_{LC} \ln P_L \ln P_C + \beta_{MC} \ln P_M \ln P_C + \delta_{pf} \ln Y_p \ln Y_f + \rho_{Lp} \ln P_L \ln Y_p + \rho_{Lf} \ln P_L \ln Y_f \\ & + \rho_{Mp} \ln P_M \ln Y_p + \rho_{Mf} \ln P_M \ln Y_f + \rho_{Cp} \ln P_C \ln Y_p + \rho_{Cf} \ln P_C \ln Y_f \end{aligned}$$

155

Description of variables

<i>Cost</i> : Maintenance cost (£/m*year)	<i>Y_p</i> : Traffic volume of passenger car (vehicles/day)
<i>L</i> : Labour cost (£/m*year)	<i>Y_f</i> : Traffic volume of large-sized car (vehicles/day)
<i>M</i> : Material cost (£/m*year)	<i>N</i> : Earthquake frequency (numbers/year)
<i>C</i> : Capital cost (£/m*year)	

156

157

(6)

158

159 The cost-share functions in terms of labour, material and capital cost can be shown in equations
 160 (7), (8) and (9) by use of Shephard's lemma (Shepherd, 1970).

$$S_L = \frac{\partial \ln Cost}{\partial \ln P_L} = \beta_L + \beta_{LL} \ln P_L + \beta_{LM} \ln P_M + \beta_{LC} \ln P_C + \rho_{Lp} \ln Y_p + \rho_{Lf} \ln Y_f$$

(7)

$$S_M = \frac{\partial \ln Cost}{\partial \ln P_M} = \beta_M + \beta_{MM} \ln P_M + \beta_{ML} \ln P_L + \beta_{MC} \ln P_C + \rho_{Mp} \ln Y_p + \rho_{Mf} \ln Y_f$$

(8)

$$S_C = \frac{\partial \ln Cost}{\partial \ln P_C} = \beta_C + \beta_{CC} \ln P_C + \beta_{CL} \ln P_L + \beta_{CM} \ln P_M + \rho_{Cp} \ln Y_p + \rho_{Cf} \ln Y_f$$

(9)

The cost-share function can be rearranged below in reference to equations (7), (8) and (9) (Subal, 1997).

$$S_i = \beta_i + \sum_j \beta_{ij} \ln P_j + \sum_l \rho_{jl} \ln Y_l$$

(10)

The sum of error terms is 0 because the sum of all cost shares is 1. Therefore, parameters in the function (7), (8) and (9) cannot be estimated because the error variance and the covariance matrix are singular. Thus, when cost-share functions are estimated at the same time, one arbitrary function needs to be removed from the three cost-share functions S_L , S_M and S_C . In other words, the three functions including the translog function (6) and two cost-share functions were used to estimate parameters, thereby allowing the removal of the arbitrary one. Moreover, it is presumed there is correlation between error terms in each function and each sample has no correlation (Bilodeau and Duchesne, 2000). This system is said to be seemingly unrelated to the regression model (SUR model) and it is estimated by the feasible generalized least squares (FGLS) estimation method. As stated above, maximum likelihood estimates can be found (Bilodeau and Duchesne, 2000).

4.2 Software

The author used MATLAB R2017a for the FGLS estimation (MATLAB, 2018).

4.3 Input data

This study uses the real data of maintenance costs for the Route 3. Along the route, one bridge is 27m long with 2 lanes and is assumed to be maintained routinely. This bridge was focused on, as shown in Figure 2 and 3. The road is a charged expressway in Tokyo's urban area and its AADT ranged from roughly 75,000 to 110,000 cars per day (during the analysis period). The structure consists of a steel girders and piers and it was built in 1967. Recently, maintenance works involving repairing damage have been frequently implemented. Labour and material costs spent past 10 years in maintenance works for the bridge were used as analysis data. The maintenance works include only works on the steel bridge structure, which greatly influences future maintenance strategy. Therefore, other maintenance works for pavements and other facilities were not analysed. Furthermore, the depreciation cost of the asset, which has been used for maintenance, was considered as a capital cost. Although it is necessary to understand construction cost at the time of constructed precisely for accurate calculation of the depreciation cost, there was no data relevant to the construction cost. However, this problem could be solved by use of a deflator. The deflator shows the ratio between two construction costs when similar buildings are constructed now and in the past. Herewith, the expressway construction cost in 1967 can be calculated by using the cost of the same structural expressway construction recently. The equation below based on the present value of the expressway bridge and relevant ratios calculates its depreciation cost defined by National tax agency in Japan (National Tax agency, 2017). The present value is calculated by use of the construction cost mentioned before and maintenance cost which increases asset value. Furthermore, the durable life of the expressway is determined by its physical life. The depreciation procedure needs to be continued until the price becomes 10% of its acquisition cost in case the expressway asset value increased.

$$\text{Depreciation cost per year} = P \times 0.9 \times 0.023$$

P: Present value

0.9: Ratio of total depreciation cost

0.023: Depreciation rate per year

For the reasons aforementioned, 3 types of costs such as labour, material and capital cost were regarded as factors of production. The price of the factors, passenger and large-sized cars' AADT, and earthquake frequency are set as explanatory variables for maintenance costs listed in Table 3. Large-sized cars are defined as coaches, large trucks, trailers and special vehicles such as construction vehicles. Although it was desirable to use vehicle load data, two types of data mentioned before were used for analysis because of having no access to axle-load data. Therefore, the results were limited to the figures for average passenger and large-sized cars without considering detailed weight classes. The intensity of earthquakes was limited to more than what people can feel, as per the Japan Meteorological Agency seismic intensity scale. The official scale does not show the scale of earthquake itself but shows the intensity of shaking caused by earthquakes at an observation point. Moreover, the scale has 10 grades specified by accelerometers. By definition, if the seismic intensity is more than 1, the earthquake can be physically felt by people. In addition, traffic volume was derived from traffic counters densely allocated along the expressway. Data gaps were assumed not to affect the results because the failures of devices and their deficits are quite small. Although Link (2005) used the number of days, which had temperature fluctuations around 0 degrees Celsius as an explanatory variable for the renewal cost in German highways, this study does not use the explanatory variables due to the relatively small amount of available data in Tokyo.

4.4 MATLAB feasible generalized least squares (FGLS) estimation

Parameter estimation was implemented by use of the translog cost function and cost share equations as explained in section 4.1. Since 10 years' data from 2007 to 2016 was analysed, a total of 30 equations were used to estimate parameters. The data and program code utilized in the estimation are listed in Figure 4 and 5.

5. Input data analysis

This section focuses on input data used in parameter estimation. This data includes the number of earthquakes, AADT of passenger and large-sized cars, and factors of production. First, number of earthquakes shown in Figure 6 is checked. The earthquakes focused are large enough to feel by human. In addition, they are only available and objective data observed in Japan Meteorological Agency (Japan Meteorological Agency, 2018). As shown in the figure, the number of earthquakes decreased from 2007 to 2009. However, it suddenly rose in 2010 and was also high in 2011. The rise was believed to be influenced by the occurrence of Great East Japan earthquake and its aftereffects. Although the earthquake occurred in March 2011, Figure 6 illustrates it in 2010 because the Japanese annual fiscal year from April to March was used. After that, the earthquake frequency decreased from 2012 to 2015, and then it slightly increased in 2016.

Second, the AADT of passenger and large-sized cars is shown in Figure 6. These two kinds of traffic have gradually decreased in volume over the last 10 years. Especially in 2010, the volume significantly decreased. A possible reason was that a new ring road was partially opened in 2010. The ring road called the Central Circular route is expressed by a red line in Figure 7 and acted as an alternative to Route 3. As a result, the traffic volume decreased. As for passenger cars, traffic volume remained at the same level from 2010 to 2016. On the other hand, traffic volume of large-sized cars continued to decrease after 2011. The Central Circular Route has possibly influenced large-sized cars more than passenger cars.

Third, factors of production focused in the research are explained. Labour and material cost showed similar movement during analysis period. This was possible because these two types of costs were mainly for maintenance works. In addition, capital costs showed increasing trend for 10 years. This movement was assumed to be highly related to expressway asset value.

Lastly, future prospects are explained. As for earthquake frequency, it is difficult to estimate it precisely. However, it is possible to estimate traffic volume to some extent. First, the Olympic Games will be held in Tokyo in 2020. Although traffic demand in Tokyo metropolitan area will be higher, Tokyo Metropolitan Government will aim to cut the traffic volume in the area during the

Olympic Games by 15 percent from general weekly levels (The Japan Times, 2018). In addition, the three ring expressways connecting the Greater Tokyo Area will be completed in the near future as shown in Figure 7 (Tokyo Metropolitan Government Bureau of Construction, 2018). These events could have effects on the traffic situation. In particular, the completion of the three ring expressways could make traffic flow much smoother and more effective (Oguchi, Chikaraishi, Iijima et al., 2016), as a result, the traffic volume in radial expressway routes such as the Route 3 will decrease after the completion of the three ring expressways.

6. Estimation Results

6.1 Parameter estimation

Table 4 shows the regression estimate results by use of the translog cost function and the cost-share functions explained in the previous section. It is assumed the results of the estimation are largely confirmed to be statistically stable without γ_p , γ_f , β_{CC} and ρ_{CP} due to standard error. On the other hand, the influence on maintenance cost by earthquake frequency and capital cost cannot be confirmed because the coefficients are too small, which means capital cost is not a supportive coefficient in this case. Moreover, since parameter γ_f is shown to be a negative value, the traffic volume of large-sized cars possibly decreases maintenance costs. Actually, traffic volume is not measured by an axle load of each vehicle but by a length of each vehicle. Generally speaking, weight directly influences on structure deterioration. Thus, the phenomenon could possibly occur because of the measuring method of traffic volume on the expressway. Furthermore, the estimation accuracy of parameter γ_f is low. Hence, additional parameter estimation is conducted afterwards.

6.2 Price elasticity

Price elasticity can be calculated from the estimated parameters. That price elasticity can be divided into the elasticity between any pair of input factors and the own-price elasticity of each factor. These two kinds of elasticities can be calculated by applying the Allen-Uzawa substitution elasticities (Uzawa, 1962).

300

$$\varepsilon_{ii} = \frac{\beta_{ii} + S_i(S_i - 1)}{S_i^2}$$

$$i = L, M, C$$

ε_{ii} : Own – price elasticities of each factor

301

(12)

$$\varepsilon_{ij} = \frac{\beta_{ij} + S_i \cdot S_j}{S_i \cdot S_j}$$

$$i, j = L, M, C$$

ε_{ij} : Substitution elasticities between any pair of input factors

302

(13)

303

304 A transition of own-price elasticities of three factors are shown in Table 5 and Figure 8 by use of
 305 parameter estimation in the previous section. As a result of the transition, labour and material
 306 costs are substitutes because of their values being less than 0, while capital cost can be
 307 understood as a complementary factor. Even if capital cost rises, the demand will increase.
 308 Ryan and Wales (1999) stated translog cost functions needed to be concave in prices, in
 309 addition, the Hessian matrix of the cost functions should be negative semidefinite as a
 310 necessary condition for concavity. This is the same as the cost minimizing condition. In other
 311 words, capital cost does not meet the cost minimizing condition. As mentioned before,
 312 parameter estimation of capital cost is still in doubt in terms of its accuracy. Thus, parameter
 313 estimation without a factor of capital cost needs to be implemented. However, as mentioned in
 314 6.1 section, the influence of capital cost is quite small. In other words, the influence can be
 315 discounted. Thus, the analysis with the parameter shown in Table 4 will also be implemented
 316 continuously. The translog function and cost share functions without a factor of cost function
 317 used in the estimation are as follows.

318

$$\begin{aligned} \ln Cost = & c + \alpha \cdot \ln N + \beta_L \ln P_L + \beta_M \ln P_M + \gamma_p \ln Y_p + \gamma_f \ln Y_f \\ & + \frac{1}{2} (\beta_{LL} \ln^2 P_L + \beta_{MM} \ln^2 P_M + \delta_{pp} \ln^2 Y_p + \delta_{ff} \ln^2 Y_f) + \beta_{LM} \ln P_L \ln P_M + \delta_{pf} \ln Y_p \ln Y_f \\ & + \rho_{Lp} \ln P_L \ln Y_p + \rho_{Lf} \ln P_L \ln Y_f + \rho_{Mp} \ln P_M \ln Y_p + \rho_{Mf} \ln P_M \ln Y_f \end{aligned}$$

319 (14)

$$S_L = \frac{\partial \ln Cost}{\partial \ln P_L} = \beta_L + \beta_{LL} \ln P_L + \beta_{LM} \ln P_M + \rho_{Lp} \ln Y_p + \rho_{Lf} \ln Y_f$$

320 (15)

$$S_M = \frac{\partial \ln Cost}{\partial \ln P_M} = \beta_M + \beta_{MM} \ln P_M + \beta_{LM} \ln P_L + \rho_{Mp} \ln Y_p + \rho_{Mf} \ln Y_f$$

321 (16)

322

323 The results of parameter estimation are listed in Table 6. First, estimation accuracy of
 324 parameters is assumed to be significantly improved more than previous estimation in terms of
 325 standard error. However, parameter tendency as the results show is quite similar to the previous
 326 estimation shown in Table 4. Thus, it cannot be stated unconditionally that the results of
 327 previous estimation have a problem in their accuracy. In addition, it is assumed traffic volume of
 328 passenger cars and maintenance cost have a proportional connection because of two reasons
 329 as follows. One is the value γ_p is greater than γ_f according to the results. The other is traffic
 330 volume of passenger cars is significantly higher than that of large-sized cars. However, the
 331 influences on maintenance cost by passenger and large-sized cars need be considered.

332

333 As for own-price elasticities, all figures illustrated in Table 7 and Figure 9 are less than 0,
 334 thereby showing the existence of the own-price elasticities over an entire period. Therefore, the
 335 results are consistent with cost minimizing conditions. On the other hand, in comparison with
 336 labour and material costs as factors of production, these two factors are close to 0 as Figure 8
 337 shows. Therefore, labour and material costs do not necessarily have price elasticities.

338

339 Secondly, the results of substitution elasticities shown in Table 8 and Figure 10 are explained.
 340 Although the figures of labour and material costs are positive, they are close to 0. Thus, these
 341 two factors of production are independent rather than substitutes. On the other hand, for
 342 reference purposes only, other substitution elasticities from previous estimations shown in
 343 Figure 10 were more than 0 over an entire period and expressed considerably similar
 344 movements. Therefore, it is assumed these two kinds of elasticities can be substitutes. The
 345 movement was highly influenced by the transition of the three cost factors.

346

347 Price elasticities are focused on in this section. Labour and material cost are independent
348 factors as for substitution elasticity. Moreover, though there is a problem about estimation
349 accuracy in capital cost, as for own-price elasticity, both labour and material cost have also
350 shown independent trends. Labour and material costs are assumed to not be substitutes nor
351 complements because of their roles, though both of them are essential for maintenance works.
352 Moreover, capital cost is assumed to have a strong relationship with the maintenance quantity
353 which influences expressway asset value. Furthermore, according to the rising quantity of
354 maintenance works as a result of Great East Japan earthquake in 2011, expressway asset
355 value, capital cost and the price elasticity have temporally increased. Demand fluctuation for
356 maintenance can influence considerably capital cost.

357

358

359 **6.3 Returns to scale (RTS)**

360 Next, returns to scale (RTS) is analysed. The definition is generally to be the proportional
361 increase in outputs that would result from a proportional increase in all inputs (Panzar and
362 Willig, 1977). The expressway focused is one of the main roads in Tokyo's central area.
363 Furthermore, its traffic volume is forecasted to fluctuate in the future due to the completion of
364 the three ring expressways and the Tokyo Olympic Games. Thus, getting a grasp of RTS is
365 important. However, there are two cases of RTS. One is a situation that only one output such as
366 traffic volume of passenger cars or large-sized cars increases N times more than before when
367 maintenance cost increases N times more than before. Another situation is all outputs increase
368 N times more than before in the same situation mentioned before. Although plural outputs such
369 as traffic volume of passenger and large-sized cars are considered, these two outputs are
370 assumed to be correlated with each other. Hence, the latter situation is more appropriate for this
371 study. The latter situation, known as overall scale economies, can be shown by transforming the
372 translog function (17). If the size of the result is less than 1, RTS is regarded to come into play
373 (Noulas, Ray and Miller, 1990). In this study, if RTS can be confirmed, less input such as
374 maintenance cost can generate same amount of output as current one.

375

$$\begin{aligned}
RTS &= \sum_l \left(\frac{\partial \ln Cost}{\partial \ln Y_l} \right) \\
&= \beta_p + \beta_f + \delta_{pp} \ln Y_p + \delta_{ff} \ln Y_f + \delta_{pf} \ln Y_p + \delta_{fp} \ln Y_f + \rho_{Lp} \ln P_L + \rho_{Lf} \ln P_L \\
&\quad + \rho_{Mp} \ln P_M + \rho_{Mf} \ln P_M + \rho_{Cp} \ln P_C + \rho_{Cf} \ln P_C
\end{aligned}
\tag{17}$$

The results are shown in Table 9 and Figure 11. The value of RTS remained close to 0 from 2007 to 2016 as is the case with the previous estimation. Therefore, existence of RTS can be found from the results because the value during the entire period has been less than 1. Hence, less maintenance cost as input can generate same traffic volume as output if the situation is same as current condition. For example, if the amount of maintenance works is increased and the works are done all at once, the maintenance cost can be reduced.

6.4 Marginal maintenance cost

Marginal cost for maintenance works is evaluated based on parameter estimation calculated in the previous section. Since traffic volume of passenger cars is considered to be the most influential factor, the relationship between traffic volume and marginal maintenance cost needs to be confirmed. If marginal maintenance cost is considerably influenced by change in traffic volume of passenger cars, current maintenance method has room to be improved for cost efficiency. However, if the change has little effect on maintenance cost, current maintenance method assumed to be cost-effective. In the calculation of marginal maintenance cost, 10 years' average data for earthquake frequency, large-sized cars AADT, labour, material and capital cost are used. The results are listed in Figure 12, which consists of the parameters by use of the renewal translog model (14) and the parameters shown in Table 4 derived from first translog model (6) as a previous estimation. The difference between these two estimations is present with or without capital cost. As a result, these two models displayed the same tendencies. First, marginal cost significantly increases between 0 and 30,000 cars per day. Then, the cost remains almost the same when traffic volume rises. Thus, even if traffic volume considerably fluctuates from its current situation of about 60,000 cars per day, it is assumed maintenance

cost will not drastically change by use of the current maintenance method. In other words, current maintenance method is assumed to be economically efficient.

7. Conclusions

The Metropolitan Expressway recently has suffered serious damage especially in the old routes. Therefore, optimal maintenance methods for the expressway have been more important than before. This study focused on maintenance cost in a steel viaduct in “Metropolitan Expressway Route 3 Shibuya Line”, and analysed the marginal maintenance cost and the influences on the maintenance cost from uncertainties such as earthquakes and future traffic volume from an econometric perspective. As for analysis method, labour, material and capital costs related to the viaduct maintenance are evaluated as input factors for a translog cost function. In addition, traffic volume of passenger and large-sized cars are used as output to calculate price elasticities of input factors, RTS and a marginal maintenance cost.

First, in parameter estimation, the result indicated traffic volume of passenger cars was the most influential factor of maintenance cost. On the other hand, this study could not confirm the influence of earthquake frequency on the maintenance cost. Although the Great Hanshin-Awaji Earthquake in 1995 actually caused destructive damage to many infrastructure facilities such as the Hanshin Expressway bridges (Miki and Sasaki, 2005), some seismic countermeasures of both current reinforced concrete and steel piers were implemented in addition to the introduction of new seismic design afterwards (Yasuda and Ogasawara, 2004). Such countermeasures are assumed to minimise the negative effects of earthquakes. As a result, it is assumed the effect of earthquakes on maintenance cost were not observed.

As for own-price elasticities, labour and material costs showed independent tendencies. Moreover, the results are quite similar those outlined by Link (2014). However, capital cost showed a complementary tendency. The tendency means the capital demand will rise later on when the cost increases. That can be easily estimated from the relationship between

depreciation cost which consists of capital cost and expressway asset value. In other words, it is assumed the results showed the actual movement of the costs well.

Furthermore, RTS was consequently confirmed as Link (2014) suggested. Therefore, current traffic volume can be maintained by use of less maintenance cost than current one in the following situation. If the amount of maintenance works is increased and the works are done all at once, the more cost-effective maintenance can be achieved.

As for marginal cost, even if traffic volume significantly fluctuates, it is highly possible maintenance cost will not change considerably. In other words, maintenance cost will not drastically change if the current maintenance method continues to be used.

Lastly, according to the analysis of the results, the current maintenance method should not be changed immediately in consideration of cost minimisation and optimal cost. Furthermore, fluctuation of traffic volume in the future can be dealt with if the number of AADT passenger cars considerably changes. On the other hand, despite it being said maintenance cost is mainly influenced by traffic volume of large-sized cars (Link 2006), the analysis results indicated traffic volume of passenger cars had the most impact on maintenance cost.. Future work includes data collection and analysis of detailed vehicle classifications in order to improve financial strategy and structure of Tokyo expressway access fee.

Acknowledgements

The authors are grateful to the advice and data provided by MECL. We wish to also thank Dr Keiichi Goto working at the Railway Technical Research Institute and my company colleagues for their dedicated cooperation and helpful advices.

References

Atkinson, S. and Halvorsen, R. (1984) Parametric Efficiency Tests, Economies of Scale, and Input Demand in U.S. Electric Power Generation, International Economic Review 25(3): pp.647-662.

461 Bottasso, A. Conti, M. (2009) Scale economies, technology and technical change in the water
 462 industry: Evidence from the English water only sector, *Regional Science and Urban*
 463 *Economics* 39(2): pp.138-147.
 464 Bilodeau, M. and Duchesne, P. (2000) Robust estimation of the SUR model, *The Canadian*
 465 *Journal of Statistics* 28(2): pp.277-288.
 466 Christensen, L., Jorgenson, D. and Lau, L. (1973) Transcendental Logarithmic Production
 467 Frontiers, *The Review of Economics and Statistics* 55(1): pp.28-45.
 468 Clark, J. and Speaker, P. (1994) Economies of scale and scope in banking: evidence from a
 469 generalized translog cost function, *Quarterly Journal of Business and Economics* 33(2):
 470 pp.3-25.
 471 Coelli, T (1995) Recent developments in frontier modelling and efficiency measurement,
 472 *Australian Journal of Agricultural Economics* 39(3): pp.219-245.
 473 Deller, S., Chicoine, D. and Walzer, N. (1988) Economies of Size and Scope in Rural Low-
 474 Volume Roads, *The Review of Economics and Statistics* 70(3): pp.459-465.
 475 Fare, R., Grosskopf, S. and Pasurka, C. (2007) Environmental production functions and
 476 environmental directional distance functions, *Energy* 32: pp.1055–1066.
 477 Feigenbaum, S. and Teeple, R. (1983) Public Versus Private Water Delivery: A Hedonic Cost
 478 Approach, *The Review of Economics and Statistics* 65(4): pp.672-678.
 479 Ferrier, G. and Lovell, C. (1990) Measuring cost efficiency in banking *Econometric and Linear*
 480 *Programming Evidence*, *Journal of Econometrics* 46: pp.229-245.
 481 Ford, J. and Warford, J. (1969) Cost functions for the water industry, *The Journal of Industrial*
 482 *Economics* 18(1): pp.53-63.
 483 Heath, R. (1995) The Kobe earthquake: some realities of strategic management of crises and
 484 disasters, *Disaster Prevention and Management: An International Journal* 4(5): pp.11-24.
 485 Japan Meteorological Agency (2018) Earthquake Information [online]. Available at:
 486 <https://www.jma.go.jp/jma/indexe.html> [Accessed 18 August 2018]
 487 Kim, H. (1987) Economies of Scale in Multi-Product Firms: An Empirical Analysis, *Economica*
 488 *New Series* 54(214): pp.185-206.
 489 Link, H. (2005) An econometric analysis of motorway renewal costs in Germany, *Transportation*
 490 *Research Part A* (40): pp.19–34.

491 Link, H. (2014) A cost function approach for measuring the marginal cost of road maintenance,
 492 Journal of Transport Economics and Policy 48(1): pp.15–33.

493 Mann, P. and Mikesell, J. (1976) Ownership and water system operation, Water Resources
 494 Bulletin 12(5): pp.995-1004.

495 Mathworks (2018) R2018a Documentation: Feasible generalized least squares [online].
 496 Available at: <https://jp.mathworks.com/help/econ/fgls.html> [Accessed 1 August 2018]

497 Metropolitan Expressway Company Limited (2015), Company Profile 2015 [online]. Available at:
 498 http://www.shutoko.co.jp/~media/pdf/english/about/corporate/booklet_profile_2015.pdf
 499 [Accessed 9 July 2018]

500 Metropolitan Expressway Company Limited (2017a), Company Profile 2016 [online]. Available
 501 at: http://www.shutoko.co.jp/~Media/pdf/index/about/profile/booklet_profile_2017.pdf
 502 [Accessed 17 August 2018]

503 Metropolitan Expressway Company Limited (2017b), Inspection Procedures for structures (in
 504 Japanese)

505 Miki, C. and Sasaki, E. (2005) Fracture in Steel Bridge due to Earthquakes, Steel Structures 5:
 506 pp.133-140.

507 Morgan, W. (1977) Investor owned vs. publicly owned water agencies: an evaluation of the
 508 property rights theory of the firm, Water Resources Bulletin 13(4): pp.775-781.

509 National tax agency in Japan (2017) No.12013 Overview of depreciation [online]. Available at:
 510 <https://www.nta.go.jp/english/taxes/individual/12013.htm> [Accessed 6 August 2018].

511 Noulas, A., Ray, S. and Miller, S. (1990) Returns to Scale and Input Substitution for Large U. S.
 512 Banks, Journal of Money Credit and Banking 22(1): pp.94-108.

513 Oguchi, T., Chikaraishi, M., Iijima, M., Oka, H., Horiguchi, R., Tanabe, J. and Mohri, Y. (2016)
 514 Advanced simulation model in the region of Tokyo metropolitan urban expressway rings,
 515 23rd ITS World Congress Melbourne Australia: pp.1-11.

516 Panzar, J. and Willig, R. (1977) Economies of Scale in Multi-Output Production, The Quarterly
 517 Journal of Economics 91(3): pp.481-493.

518 Podolny, J. (1993) A Status-Based Model of Market Competition, American Journal of Sociology
 519 98(4): pp.829-872.

- Pulley, L. and Braunstein, Y. (1992) A composite cost function for multiproduct firms with an application to economies of scope in banking, *The Review of Economics and Statistics* 74(2): pp.221-230.
- Ryan, D. and Wales, T. (1999) Imposing local concavity in the translog and generalized Leontief cost functions, *Economics Letters* 67: pp.253-260.
- Shepherd, W. (1970) *Theory of Cost and Production Functions*. Princeton Press, Princeton.
- Subal, K. (1997) Modeling allocative inefficiency in a translog cost function and cost share equations: An exact relationship, *Journal of Econometrics* 76 (1-2): pp.351-356.
- The Japan Times (2018) 15 percent cut in traffic eyed during 2020 Tokyo Olympics [online]. Available at: <https://www.japantimes.co.jp/news/2018/01/11/national/15-percent-cut-traffic-eyed-2020-tokyo-olympics/#.W3rZHuj0k2w> [Accessed 18 August 2018]
- Tokyo Metropolitan Government Bureau of Construction (2018) Construction of Road [online]. Available at: <http://www.kensetsu.metro.tokyo.jp/english/jigyo/road/01.html> [Accessed 3 August 2018]
- Urakami, T. and Parker, D. (2011) The Effects of Consolidation amongst Japanese Water Utilities: A Hedonic Cost Function Analysis, *Urban Studies* 48(13): pp.2805-2825.
- Uzawa, H (1962) Production Functions with Constant Elasticities of Substitution, *The Review of Economic Studies* 29(4): pp.291-299.
- Viton, P. (1981) A Translog Cost Function for Urban Bus Transit, *The Journal of Industrial Economics* 29(3): pp.287-304.
- Yasuda, S. and Ogasawara, M. (2004) Studies on several countermeasures against liquefaction-induced flow and an application of a measure to existing bridges in Tokyo, *Journal of Japan Association for Earthquake Engineering* 4(3): pp.370-376.

Figure captions

- Figure 1. The map of Metropolitan Expressway (permission obtained from Metropolitan Expressway Company Limited)
- Figure 2. The bridge span focused on in the study (ground plan) (permission obtained from Metropolitan Expressway Company Limited)
- Figure 3. The bridge span focused on in the study (cross section) (permission obtained from Metropolitan Expressway Company Limited)
- Figure 4. Data list for parameter estimation (permission obtained from the author)

552 Figure 5. Program code for parameter estimation (permission obtained from the author)

553 Figure 6. AADT and number of earthquakes (permission obtained from the author)

554 Figure 7. The three ring expressways (permission obtained from Tokyo Metropolitan

555 Government)

556 Figure 8. Own-price elasticities of each factor (permission obtained from the author)

557 Figure 9. Own-price elasticities of labour and material factors (permission obtained from the

558 author)

559 Figure 10. Substitution elasticities between labour, material and capital cost (permission

560 obtained from the author)

561 Figure 11. Returns to Scale (RTS) (permission obtained from the author)

562 Figure 12. Marginal maintenance cost per meter (permission obtained from the author)

563

564 **Table captions**

565 Table 1. 4 grades of damage in inspection (permission obtained from Metropolitan Expressway

566 Company Limited)

567 Table 2. 3 types of damage and their effects on performance of structures (permission obtained

568 from Metropolitan Expressway Company Limited)

569 Table 3. Descriptive analysis of 1 span in Metropolitan Expressway Route 3 (permission

570 obtained from Metropolitan Expressway Company Limited)

571 Table 4. Results of the translog model for Metropolitan Expressway maintenance cost

572 (permission obtained from the author)

573 Table 5. Results of the own-price elasticities of each factor (permission obtained from the

574 author)

575 Table 6. Results of the renewal translog model for the maintenance cost (permission obtained

576 from the author)

577 Table 7. Results of own-price elasticities of labour and material factors (permission obtained

578 from the author)

579 Table 8. Results of substitution elasticities between labour and material cost (permission

580 obtained from the author)

581 Table 9. Returns to Scale (RTS) (permission obtained from the author)