

Value Added Strategy for Unplanned Rail Track Inspections

Osman, Mohd Haniff; Kaewunruen, Sakdirat

DOI:

[10.3390/proceedings2161141](https://doi.org/10.3390/proceedings2161141)

License:

Creative Commons: Attribution (CC BY)

Document Version

Publisher's PDF, also known as Version of record

Citation for published version (Harvard):

Osman, MH & Kaewunruen, S 2018, 'Value Added Strategy for Unplanned Rail Track Inspections', *Proceedings*, vol. 2, no. 16. <https://doi.org/10.3390/proceedings2161141>

[Link to publication on Research at Birmingham portal](#)

Publisher Rights Statement:

Checked for eligibility: 25/09/2018

First published in:

Proceedings 2018, 2(16), 1141; <https://doi.org/10.3390/proceedings2161141>

General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

Value Added Strategy for Unplanned Rail Track Inspections †

Mohd Haniff Bin Osman ^{1,2,*} and Sakdirat Kaewunruen ¹

¹ School of Engineering, University of Birmingham, Edgbaston B15 2TT, UK; s.kaewunruen@bham.ac.uk

² Faculty of Engineering and Built Environment, Universiti Kebangsaan Malaysia, Bangi 43600, Malaysia

* Correspondence: mxo574@bham.ac.uk; Tel.: +44-075-497-51051

† Presented at 2018 International Symposium on Rail Infrastructure Systems Engineering (i-RISE 2018), Brno, Czech Republic, 5 June 2018.

Published: 17 September 2018

On-demand (or unplanned) track inspection could be due to a disruption in a track geometry recording car [1–5]. A proper selection of input- and output-memory order which is required for prediction of *missing* track measurement using a nonlinear autoregressive model with external series (NARX) is expected to create value added to the inspection decision.

For a M -meter length of unit track section, there could be sequence of track (measurement) points, denoted as $x_i; i = 1, \dots, m$ where $m = M/r$. Distance between two adjacent points is r meter and its value depends on the sampling rate employed by a track recording car during track measurement (inspection). Each x_i is assigned with amplitude of track irregularity e.g., longitudinal level. Here, it is expressed as $y(x_i)$. In the event of disruption, a predicted value of $y(x_i)$ is demanded as risk aversion towards unplanned train speed restrictions. The NARX model is formulated to predict track irregularity of a track section and is given as follows:

$$\tilde{y}(x_i) = f\left(y(x_{i-1}), \dots, y(x_{i-d_y}), u(x_{i-1}), \dots, u(x_{i-d_u})\right) \quad (1)$$

where $u(x), y(x) \in \mathbb{R}$ denote, respectively, the input and output of the model at discrete unit step i , while $d_y \geq 1$ and $d_u \geq 1$ are the input-memory and output-memory orders [6]. Performance of the NARX model is however sensitive to a selection of d_y and d_u . In the context of our study, the corresponding selection problem can be solved by determining a segment of size L denoted as $S = \{x_j, \dots, x_{j+L}\}; j, j + L \leq m$ which minimizes the weighted error function $wMSE$ given as follows [7].

$$wMSE(x_i) = (1 - \gamma) \sum_{t=j+L+1}^{j+L+n} (\tilde{y}(x_t) - y(x_t))^2 + \gamma \frac{1}{n} \sum_{r=1}^n w_r^2 \quad (2)$$

where γ is the performance ratio, w the network weights and biases and n the number of hidden nodes in the network. The function $wMSE$ represents the performance of NARX model in Equation (1) to predict track irregularity for a unit track section $[x_{j+L+1}, x_{j+L+n}]$.

An example is prepared to demonstrate benefits of analyzing the effect of proper selection of segment S . Here, the NARX model takes measurement of track gauge, alignment (left and right) and the value of recent change in the longitudinal level calculated from two consecutive track inspections as external variables. An output of the model is longitudinal track irregularity over a $M = 100$ m unit track section. Related data series in the example is plotted in Figure 1. In this example, the value of L was 10 (is equivalent to 5 m track). Thirteen values of x_j were selected as candidates for the segment S and their model performance is displayed in Figure 2. Results show the existence of variation in the performance of prediction model due to a different choice of position of S .




Figure 1. Collection of data series used in the example. The bottom three plots associate with $u(x)$ in the Equation (1).




Figure 2. Model performance averaged over 30 simulation runs for 11 choices of S_i .

Disruptions in track geometry inspection create an opportunity to deliver value added to track inspections program. This goal can be achieved through an effective decision in assigning on-demand (manual) inspection to an affected track area. A case of *missing* longitudinal track irregularity where the missed values can be predicted by NARX is presented. The simulation results demonstrate that the segment selection step in NARX is beneficial to obtain rich information from unplanned track inspection. More simulation works are however required in future to strengthen the claim/suggestion.

Acknowledgments: The authors are sincerely grateful to European Commission for the financial sponsorship of the H2020-RISE Project No. 691135 “RISEN: Rail Infrastructure Systems Engineering Network” [8].

References

1. Bin Osman, M.H.; Kaewunruen, S.; Min, A.; Dindar, S. Disruption: A new component in the track inspection schedule. In Proceedings of the 2016 IEEE International Conference on Intelligent Rail Transportation (ICIRT), Birmingham, UK, 23–25 August 2016; pp. 249–253.
2. Sa’adin, S.L.B.; Kaewunruen, S.; Jaroszweski, D. Operational readiness for climate change of Malaysia high-speed rail, *Proc. Inst. Civ. Eng. Transp.* **2016**, *169*, 308–320
3. Kaewunruen, S.; Sussman, J.M.; Einstein, H.H. Strategic framework to achieve carbon-efficient construction and maintenance of railway infrastructure systems. *Front. Environ. Sci.* **2015**, *3*, 6, doi:10.3389/fenvs.2015.00006
4. S’adin, S.L.B.; Kaewunruen, S.; Jaroszweski, D. Risks of climate change with respect to the Singapore-Malaysia high speed rail system, *Climate* **2016**, *4*, 65, doi:10.3390/cli4040065
5. Kaewunruen, S.; Remennikov, A.M. Relationships between wheel/rail interface impact and railseat flexural moment of railway prestressed concrete sleepers, In Proceedings of 2007 SEM Annual Conference and Exposition on Experimental and Applied Mechanics, Springfield, MA, USA, 4–6 June 2007.
6. Siek, M.; Solomatine, D. Chaotic model with data assimilation using NARX network. In Proceedings of the International Joint Conference on Neural Networks, Atlanta, GA, USA, 14–19 June 2009; pp. 2928–2935.

7. Burden, F.; Winkler, D. Bayesian regularization of neural networks. *Methods Mol. Biol.* **2008**, *458*, 25–44.
8. Kaewunruen, S.; Sussman, J.M.; Matsumoto, A. Grand Challenges in Transportation and Transit Systems. *Front. Built Environ.* **2016**, *2*, 4, doi:10.3389/fbuil.2016.00004



© 2018 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).